

QuickKleen™ Performance Fiber Cleaner



TECHNICAL DATA SHEET

Description:

QuickKleen™ Fiber Cleaner is formulated for fast cleaning of high-speed fiber and specialty optics. It quickly penetrates precision parts to lift drywall dust, buffer gel, lint, finger prints, and oils. The excellent cleaning capabilities of QuickKleen™ minimize dB losses to maximize optical network performance.

QuickKleen™ Fiber Cleaner evaporates quickly without residue. The fast-drying character means solvent is not trapped in the connector to reduce signal loss. QuickKleen™ dissipates static and removes surface charge so that the surface is less likely to be re-contaminated. QuickKleen™ is non-flammable and safe to use.

QuickKleen™ Fiber Cleaner is packaged in an easy-to-use pump sprayer that allows precise cleaner application, which limits waste and contamination. Polywater's non-woven FiberKleen™ towelettes trap dirt and absorb contaminants from high-speed fiber and optical equipment. A smooth wiping surface and durable material promote easy, effective cleaning.

Performance Properties:

QuickKleen™ Fiber Cleaner is a high-performance optical cleaner. QuickKleen™ removes a broad variety of endface contaminants.

<u>Soil Type</u>	<u>Cleaning Effectiveness</u>
Dry/Ionic Soil (dust, salt)	Excellent
Wet/Non-Ionic Soil (oil, buffer gel)	Excellent
Combination Soil	Excellent

QuickKleen™ Fiber Cleaner has been tested to the rigorous standards of Telcordia GR 2923-CORE, "Generic Requirements for Fiber Optic Connector Cleaning Products."



Product Benefits:

- Evaporates Quickly
- Excellent Solvency
- No Residue
- No Streaking
- Dissipates Static
- Non-Flammable
- Easy to Transport

End Use:

QuickKleen™ Fiber Cleaner is an excellent choice for cleaning precision fiber-optic components such as:

- Endfaces
- Single-mode Fiber
- Multi-mode Fiber
- Ferrules
- Bulkheads
- Lenses, Mirrors

Approvals:

- Meets Telcordia GR 2923-CORE, "Generic Requirements for Fiber Optic Connector Cleaning Products."
- RoHS and WEEE compliant.

Physical Properties:

QuickKleen™ Fiber Cleaner is a high purity, optical grade cleaner.

<u>Property</u>	<u>Result</u>
Residue	< 100 ppm
Flashpoint (ASTM D93)	None
Initial Boiling Point	129°F (54°C)
Specific Gravity	1.49
Evaporation Rate	Fast

Environmental Impact:











<u>Property</u>	<u>Result</u>
VOC Content	Exempt
Global Warming Potential	Does not contain global warming compounds
Ozone Depletion Potential	0.03
CFC, HCFC, HFC Content:	None
RCRA	Not regulated as hazardous waste
CERCLA/SARA Status	Not regulated as a hazardous substance
RoHS and WEEE	Compliant
REACH	Compliant

Safety:

QuickKleen™ Fiber Cleaner has minimal toxicity and does not contain any listed carcinogens. Good industrial hygiene practice and appropriate precautions should be employed during use. See MSDS for specific details.

Cleaning Properties:

QuickKleen™ Fiber Cleaner removes a broad range of contaminants from fiber connectors. To prove this, reference reflectance and transmitted power is measured on an unsoiled test connector at 1310 nm, 1550 nm and 1625 nm. Then the near-end connector plug is removed and soiled according to standard¹. Connector end adapter is cleaned using recommended procedure. Insertion loss and reflectance are measured and compared to control. An electronic image of each cleaning is recorded.

<u>Soil</u>	<u>Image – Soiled</u>	<u>Image – 1st Cleaning</u>
Gypsum		
Carbon Black		
Olive Oil		
Gypsum/ Buffer Gel		
Gypsum/ 10W30 Oil		

<u>Soil</u>	<u>Insertion Loss</u>	<u>Reflectance</u>
Gypsum	Pass (<0.05 dB loss)	Pass (<2 dB change)
Carbon Black	Pass (<0.05 dB loss)	Pass (<2 dB change)
Olive Oil	Pass (<0.05 dB loss)	Pass (<2 dB change)
Gypsum/Buffer Gel	Pass (<0.05 dB loss)	Pass (<2 dB change)
Gypsum/10W30 Oil	Pass (<0.05 dB loss)	Pass (<2 dB change)

¹ Tested using methods from Telcordia GR-2923-CORE, "Generic Requirements for Fiber Optic Connector Cleaning Products."

Compatibility:

QuickKleen™ Fiber Cleaner is compatible with most common plastics and rubbers.

Polycarbonate:

Injection-molded plaques of polycarbonate are cut into bars, 2½ inch by ½ inch. Samples are bent in a three-point fixture. Percent strain is calculated based on the bar thickness and the radius of curvature.

“Strain limit” is the greatest percent strain where no stress cracking occurs. A strain limit greater than 0.5% indicates strain resistance.

Strain Limit > 0.5%

QuickKleen™ Fiber Cleaner shows good compatibility with polycarbonate.

Cladding:

Fiber cladding (Corning Cable) is firmly wiped 5 times with a cleaner-saturated towel. Towel and cable are visually inspected for cladding transfer or damage.

Cladding shows no visible damage.

QuickKleen™ Fiber Cleaner shows good compatibility with fiber cladding.

Soak Testing:

Materials are immersed in QuickKleen™ Fiber Cleaner for an hour at 20°C (68°F). Rubbers may swell slightly, but will return to their original state once the cleaner evaporates.

<u>Plastic</u>	<u>Compatibility</u>
Nylon 66	Excellent
Polycarbonate	Excellent
Polyethylene (HDPE)	Excellent
Polyethylene (LDPE)	Excellent
PVC	Excellent

<u>Rubber</u>	<u>Compatibility</u>
Silicone Rubber	Excellent
EPDM	Excellent

Usage Directions:

QuickKleen™ Fiber Cleaner is best used with the combination wet - dry cleaning procedure recommended in Telcordia GR-2923-CORE. Microfiber towels (DT-D175) and holder (FC-HOLDER), available from American Polywater Corporation work well with this method.

A light spray of cleaner is placed on the towel. Preferred cleaning motion is a straight line motion, drawing the endface through the wetted portion of the towel, and then through a clean portion of a second dry towel. Use of the FC-HOLDER optimizes the cleaning process. Swabs may be dampened on the wetted portion of the towel in order to clean the bulkhead or equipment.

Application Properties:

Temperature Use Range:

20°F to 120°F (-5°C to 50°C)

Storage and Shelf Life:

Keep containers tightly closed when not in use. Shelf life is 2 years.

Packaging:

QuickKleen™ Fiber Cleaner is packaged in a safety sealed container that resists spills, leaks and contamination. The 2-fluid-ounce spray bottle has over 500 uses.

Microfiber Towels:

FiberKleen™ Dry Towels offer high absorbency and are made from non-linting, non-fraying ultra-clean material. This specialty, microfiber fabric is engineered for optimum particle entrapment. The durable towel has a smooth surface for easy cleaning. It meets Telcordia Specification.



Convenient Kit Packaging and Cleaning Accessories

Model Specification:

The statement below may be inserted into a customer specification to help maintain engineering standards and ensure work integrity.

The fiber cleaner shall be effective on both ionic and non-ionic soils. It shall meet the cleaning criteria of Telcordia GR 2923-CORE, "Generic Requirements for Fiber Optic Connector Cleaning Products." It shall contain an oxygenated solvent component for static dissipation.

The cleaner shall be fast evaporating and non-flammable. It shall leave minimal residue of less than 100 ppm. The cleaner shall be compatible with fiber optic components. It shall not stress crack polycarbonate and shall have a strain limit greater than 0.5%.

The cleaner shall not contain an aerosol propellant. It shall be packaged in a plastic bottle that allows cleaner to be dispensed in a fine mist spray pattern.

Order Information:

Cat #	Package Description
QC-2LP	2-oz QuickKleen™ Fiber Cleaner Finger Sprayer
QC-KIT2	QuickKleen™ Fiber Cleaner Kit: 2 QC-2LP 1 DT-D175 1 FC-HOLDER 1 SWB-250F100
DT-D175	175 microfiber towels in a sealed plastic dispenser pack with cleaning pad
FC-HOLDER	Dual towel holder with 20 slots for precision wet-dry cleaning
DT-D175H	FiberKleen™ Microfiber Towel Kit: 1 DT-D175 1 FC-HOLDER
SWB-250F100	2.5 mm FiberKleen™ foam swab (100 pack)
SWB-125F10	1.25 mm FiberKleen™ foam swab (10 pack)
SWB-C100	FiberKleen™ cotton swab (100 pack)
SWB-V100	V Groove FiberKleen™ foam swab (100 pack)
SWB-M100	Mirror FiberKleen™ foam swab (100 pack)

Copyright © 2011. American Polywater Corporation. All Rights Reserved

Important Notice: The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct, indirect, or consequential damages resulting from product's use, regardless of the legal theory asserted.

Lit-QCTECHSPEC/1-12/GH

Makers of Polywater® and Dyna-Blue® Cable Lubricants
and Pull-Planner™ Software

**American
Polywater®
Corporation**

<http://www.polywater.com>(URL)

custserv@polywater.com(e-mail)

P.O. Box 53
Stillwater, MN 55082
U.S.A
1-800-328-9384
1-651-430-2270