

# SAFETY DATA SHEET – SET

## UPR Pole Repair™ No Flow Type UPR-NF Kit

**Product ID numbers:** UPR-NFKIT4, UPR-NFKIT12, UPR-NF6B10  
UPR-NFXXX (where XXX is the package code.)

Date Compiled: October 11, 2018



### Supplier/Manufacturer:

#### American Polywater Corporation

11222 - 60th Street North  
Stillwater, MN 55082 USA  
Tel: 1-651-430-2270  
Email: sds@polywater.com

### Emergency telephone numbers

INFOTRAC: 1-800-535-5053 (USA) 1-352-323-3500 (INT'L)

This product is a kit or a multi-part product with independent components. An SDS for each component is included. Do not separate SDSs.

### Contains

UPR-NF PoleRepair NO FLOW Part A SDS  
UPR-NF PoleRepair NO FLOW Part B SDS

SDSs are classified according to USA OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).

Each Kit may or may not contain all SDS components

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.

# SAFETY DATA SHEET

## 1. Identification of the substance/mixture and of the company

### 1.1 Product identifier

**Product Name:**  
**UPR Pole Repair™ No Flow**  
**UPR-NF (Part A) 10841A**

**Product ID numbers:** UPR-NFKIT4, UPR-NFKIT12, UPR-NF6B10;  
UPR-NFXXX (where XXX is the package code.)

### 1.2 Relevant identified uses of the mixture and uses advised against

**Identified uses:** Sealant, wood fill and pole repair, two-part material

**List of advices against:** Not applicable.

### 1.3 Details of the supplier of the safety data sheet

**Supplier/Manufacturer:**

**American Polywater Corporation**  
11222 - 60th Street North  
Stillwater, MN 55082 USA  
Tel: 1-651-430-2270  
Email: sds@polywater.com

### 1.4 Emergency telephone numbers

USA (supplier)  
+1-651-430-2270

INFOTRAC: 1-800-535-5053 (USA) 1-352-323-3500 (INT'L)

## 2. Hazards Identification


### 2.1 Classification of the substance or mixture

**Classification according to USA OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).**

Acute Toxicity, Cat 4; H332  
Skin Irritation, Cat 2; H315  
Eye Irritation, Cat 2A; H319  
Respiratory Sensitization, Cat 1; H335  
Skin Sensitization, Cat 1; H317  
Target Organ Toxicity (single exposure), Cat 3  
Target Organ Toxicity (repeated exposure), Cat 2; H373

### 2.2 Label elements

**Contains:** Polymeric diphenylmethane diisocyanate; 4,4'-Diphenylmethane diisocyanate (MDI)



**Pictograms:**

**Signal word:** Danger

**Hazard Statements:**

H332 Harmful if inhaled.  
H315 Causes skin irritation.

H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated inhalative exposure.

**Precautionary Statements:**

P260	Do not breathe fumes.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing and eye protection.
P284	In case of inadequate ventilation wear respiratory protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P304 + P340	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical attention.
P337 + P313	If eye irritation persists: Get medical attention.
P342 + P311	If experiencing respiratory symptoms: Call a poison center or doctor.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents/container in accordance with local and national regulations.

**Notes:** 4,4'-methylenediphenyl diisocyanate (MDI) has not been designated as a carcinogen by IARC, NTP, ACGIH, OSHA, or the EPA. There are inadequate human carcinogenicity data, and only limited animal data. Additionally, the IARC Working Group noted that tumorigenic effects observed in animals may be attributed to non-specific particle effect (IARC monograph 71). We have not classified substance as a carcinogen, but recommend that users avoid inhalation of vapor above exposure limits.

**2.3 Other hazards:** No information available.

### 3. Composition/Information on Ingredients

<u>Component</u>	<u>CAS #</u>	<u>EC #</u>	<u>Wt. %</u>
Polymeric diphenylmethane diisocyanate	9016-87-9		30 - 60
4,4'-Diphenylmethane diisocyanate (MDI)	101-68-8	202-966-0	30 - 60
Phosphoric Acid, Triethyl Ester	78-40-0	201-114-5	1 - 5

### 4. First Aid Measures

#### 4.1 Description of first aid measures

<b>Eye Contact:</b>	Immediately flush eyes with large quantity of water for 15 minutes. Seek medical attention.
<b>Skin Contact:</b>	Remove contaminated clothing; flush skin thoroughly with soap and water. If irritation occurs, seek medical attention.
<b>Inhalation (Breathing):</b>	If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention.
<b>Ingestion (Swallowing):</b>	If swallowed, rinse mouth and drink plenty of water. Do not induce vomiting. If patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person. Do not leave victim unattended. Seek medical attention.

#### 4.2 Most important symptoms and effects, both acute and delayed

May cause allergic skin and respiratory reaction. Refer to Section 11 for more information.

#### 4.3 Indication of immediate medical attention and special treatment needed.

No information available.

### 5. Firefighting Measures

**5.1 Extinguishing media:**

Water Fog, Carbon Dioxide, Dry Chemical or Foam.

**5.2 Special hazards arising from the substance or mixture**

**Hazardous decomposition and by-products:**

Carbon monoxide, hydrogen cyanide, nitrogen oxides, aromatic isocyanates, gases/vapors.

**5.3 Advice for firefighters**

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be used to cool fire exposed container to prevent pressure build-up and possible auto-ignition or rupture.

**6. Accidental Release Measures**

**6.1 Personal precautions, protective equipment and emergency procedures:**

Wear full protective clothing, including appropriate respiratory protection.

**6.2 Environmental precautions:**

Prevent from entering waterways.

**6.3 Methods materials for containment and cleaning up:**

Spills expected to be small quantities. Collect excess material with absorbents or wipe with dry towels. Wash with a dilute ammonia solution.

**6.4 Reference to other sections:**

Refer to Sections 4, 5, 8, and 13 for more information.

**7. Handling and Storage**

**7.1 Precautions for safe handling**

Use and store this product with adequate ventilation. Avoid inhalation of vapors and personal contact with the product. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Wash thoroughly after handling. Wash contaminated clothing before reuse. For industrial or professional use only.

**7.2 Conditions for safe storage, including incompatibilities**

Keep containers cool, dry, and away from sources of ignition. Keep cartridges capped and sealed. Protect from freezing. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

**7.3 Specific end uses**

See technical data sheet on this product for further information.

**8. Exposure Controls / Personal Protection**

**8.1 Control parameters**

**Exposure limits and recommendations:**

Country/Source	Component	Long-term exposure limit 8 hr OEL, TWA	Short-term (ceiling) exposure limit – 15 min
USA – ACGIH TWA	4,4'-Diphenylmethane diisocyanate (MDI)	0.005 ppm	0.02 ppm
USA – OSHA OEL	4,4'-Diphenylmethane diisocyanate (MDI)	--	0.02 ppm
USA – NIOSH REL	4,4'-Diphenylmethane diisocyanate (MDI)	0.005 ppm	0.02 ppm
Canada (Ontario)	4,4'-Diphenylmethane diisocyanate (MDI)	0.005 ppm	0.02 ppm
Canada (Québec)	4,4'-Diphenylmethane diisocyanate (MDI)	0.005 ppm	--
Canada (British Columbia)	4,4'-Diphenylmethane diisocyanate (MDI)	0.005 ppm	0.01 ppm
Canada (Alberta)	4,4'-Diphenylmethane diisocyanate (MDI)	0.005 ppm.	--

Canada (Alberta)	Polymeric diphenylmethane diisocyanate	0.005 ppm	--
Canada (Saskatchewan)	4,4'-Diphenylmethane diisocyanate (MDI)	0.005 ppm	0.015 ppm
Canada (Yukon)	4,4'-Diphenylmethane diisocyanate (MDI)	0.02 ppm	--

ACGIH, OSHA and NIOSH have not established any OELs for Polymeric diphenylmethane diisocyanate (pMDI)

**8.2 Exposure controls**

**Respiratory protection:**

Use with adequate ventilation to keep vapor concentration below acceptable limits. Observe OSHA standard 29 CFR 1910-94, 1910.107, 1910.108. Product dispensed through a static mixer and used as directed emits less than 0.001 ppm MDI vapor as tested by OSHA 47. Ventilation is not required for standard use. If product is use in a way that ventilation is not adequate, use approved chemical/mechanical filters designed to remove a combination of particulate and organic vapors in open and restricted areas. Use approved airline type respirators or hoods in confined areas. Observe OSHA standard 29 CFR 1910.134.

**Protective gloves:**

The use of chemically resistant gloves is recommended to prevent skin contact. Suitable materials include neoprene, butyl rubber, Viton, Buna N, and chlorinated polyethylene.

**Eye protection:**

Safety glasses recommended.

**Other protective equipment:**

Wear suitable protective clothing. Use protective cream if skin contact is likely. Remove and wash contaminated clothing before reuse. Discard contaminated shoes.

**9. Physical and Chemical**

**9.1 Information of basic physical and chemical properties**

<b>Appearance:</b>	Brown liquid
<b>Odor threshold:</b>	Faint, aromatic odor
<b>pH:</b>	Does not apply
<b>Freezing point:</b>	3°C
<b>Boiling point:</b>	200°C
<b>Flash point:</b>	428°F / 220°C (open cup)
<b>Evaporation rate:</b>	Not available
<b>Flammability (solid, gas):</b>	Does not apply
<b>Upper/lower flammability or explosive limits:</b>	Not available
<b>Vapor pressure:</b>	.00016 mm Hg @ 20°C
<b>Vapor density (Air = 1):</b>	1.22 g/cm <sup>3</sup>
<b>Specific gravity (H<sub>2</sub>O = 1):</b>	1.22 @ 25°C
<b>Solubility in water:</b>	Reacts
<b>Partition coefficient: n-octanol/water:</b>	Not available
<b>Auto-ignition temperature:</b>	> 250°C (1112°F)
<b>Decomposition temperature:</b>	Not available
<b>Viscosity:</b>	200 mPas @ 25°C / 77°F

**9.2 Other Information**

<b>Volatiles (Weight %):</b>	0%
<b>VOC Content:</b>	0 g/l

**10. Stability and Reactivity**

**10.1 Reactivity:**

Reacts with water, reacts with substances which contain active hydrogen.

**10.2 Chemical stability:**

Stable

**10.3 Possibility of hazardous reactions:**

Hazardous reactions will not occur under normal transport or storage conditions.

**10.4 Conditions to avoid:**

Avoid freezing, high temperatures, flame, high humidity and water contamination.

**10.5 Incompatible materials :**

Water, alcohols, amines, acids, alkalis, metal compounds.

**10.6 Hazardous decomposition products:**

Carbon monoxide, hydrogen cyanide, nitrogen oxides, aromatic isocyanates, gases/vapors.

**11. Toxicological Information**

**11.1 Information on toxicological effects:**

**Acute toxicity**

**Eye contact:**

Direct eye contact with material or vapors may cause eye irritation.

**Skin contact:**

Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material. Allergic skin reaction symptoms include redness, swelling, blistering and itching.

**Irritation and Sensitization Potential:**

Product may be irritating to skin and eyes.

**Inhalation (Breathing):**

Material has low vapor pressure and inhalation hazard is expected to be minimal. Vapor exposure may cause irritation of the nose and throat. Symptoms may include burning sensation, coughing and shortness of breath, or other signs of respiratory distress. May cause allergic respiratory reaction below exposure guideline in susceptible individuals.

**Ingestion:**

Ingestion may cause irritation of the gastrointestinal tract.

**Toxicity to Animals:**

4,4'-Diphenylmethane diisocyanate (MDI):	LD <sub>50</sub> (oral rat) >2,000 mg/kg
	LD <sub>50</sub> (dermal rabbit) >9,400 mg/kg
	LC <sub>10</sub> (inhl rat) 2.24 mg/m <sup>3</sup> , 1 hour, aerosol form

**Aspiration Hazard:**

No aspiration hazard expected.

**Chronic Exposure:**

**Reproductive Toxicity:** Not available.

**Mutagenicity:** Not available.

**Teratogenicity:** Not available.

**Specific Target Organ Toxicity (STOT)** Contains material which causes damage to the upper respiratory tract.

**Toxicologically Synergistic Products:** Not available.

**Carcinogenic Status:** This substance contains components identified as IARC Category 3, not classifiable.  
4,4'-methylenediphenyl diisocyanate (MDI) has not been designated as a carcinogen by IARC, NTP, ACGIH, OSHA, or the EPA. There are inadequate human carcinogenicity data, and only limited animal data. Additionally, the IARC Working Group noted that tumorigenic effects observed in animals may

be attributed to non-specific particle effect (IARC monograph 71). We have not classified substance as a carcinogen, but recommend that users avoid inhalation of vapor above exposure limits.

**Respiratory/Skin Sensitization**

May cause sensitization by inhalation and skin contact..

**12. Ecological Information**

**12.1 Toxicity:**

**Aquatic Toxicity:**

- 4,4'-Diphenylmethane diisocyanate (MDI): LC<sub>50</sub> (96 hr): > 1,000 mg/l Brachydanio rerio (fish)  
OECD Guideline 203 static
- 4,4'-Diphenylmethane diisocyanate (MDI): EC<sub>50</sub> (24 hr): > 1,000 mg/l Daphnia magna (invertebrate)  
OECD Guideline 202, part 1 static
- 4,4'-Diphenylmethane diisocyanate (MDI): EC<sub>50</sub> (72 hr): 1,640 mg/l Green algae (aquatic plants)  
OECD Guideline 201 static

**12.2 Persistence and degradability:**

Elimination information:  
<10% BOD of the ThOD (28d)  
(OECD Guideline 302 C, aerobic, activated sludge)  
Under test conditions, poorly biodegradable.

**12.3 Bioaccumulation potential:**

Accumulation in organisms is not to be expected.

**12.4 Mobility in soil:**

Adsorption to solid soil phase is not expected

**12.5 Results of PBT and vPvB Assessment:**

This product is not, nor does it contain a substance that is a PBT or vPvB.

**12.6 Other adverse effects:**

None known.

**13. Disposal Considerations**

Dispose of product in accordance with National and Local Regulations.

**14. Transport Information**

- UN Number:** Not Listed
- UN Proper shipping name:** Not Applicable
- Transport hazard class(es):** Not Applicable
- Packing group:** Not Applicable
- Environmental hazards:** None known
- Special precautions:** None known
- TDG:** Not Regulated
- ICAO/IATA-DGR:** Not Regulated
- IMDG:** Not Regulated
- ADR/RID:** Not Regulated

**15. Regulatory Information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**USA Federal and State**

All components are listed on the TSCA inventory.

<b>Hazard Categories for SARA Section 311/312 Reporting</b>	<u>Acute</u> Yes	<u>Chronic</u> Yes	<u>Fire</u> No	<u>Pressure</u> No	<u>Reactive</u> No
---	---------------------	-----------------------	-------------------	-----------------------	-----------------------

<u>Components</u>	<u>CERCLA/SARA Sec 302 Hazardous Substance RQ</u>	<u>EHS TPQ</u>	<u>SARA Sec. 313 Toxic Release</u>
-------------------	---	----------------	------------------------------------

4,4'-Diphenylmethane diisocyanate (MDI)	Yes (5,000 lbs)	No	Yes (1%)
Polymeric diphenylmethane diisocyanate	No	No	Yes (1%)

**NFPA Ratings:**

Health:	2
Fire:	1
Reactivity:	1

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

**California Proposition 65**

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm or has been assessed to be below OEHHA Safe Harbor exposure levels required for labeling.

**European Union**

Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Contains no substance on the REACH candidate list  $\geq 0.1\%$  SCL. Does not contain notified substances from the ELINCS List, Directive 92/32/EEC. Meets labeling and kitting requirements found in Entry 56 of Annex XVII.

**Canada**

All components are listed on the DSL inventory.  
This product has been classified according to the hazard criteria of the CPR.

**Australia**

All components are listed on the AICS.  
Contains 4,4'-Diphenylmethane diisocyanate (MDI) listed on the National Pollutant Inventory (NPI)  
Hazardous according to criteria of NOHSC Australia.

**15.2 Chemical Safety Assessment**

No chemical safety assessment has been carried out for the mixture by the supplier.

<b>16. Other Information</b>
------------------------------

**Abbreviations and acronyms:**

- OSHA = Occupational Safety and Health Administration
- CLP = Classification, Labeling and Packaging Regulation
- STOT = Specific Target Organ Toxicity
- LD<sub>50</sub> = Median Lethal Dose
- DNEL = Derived No Effect Level
- ACGIH = American Conference of Governmental Industrial Hygienists
- TSCA = Toxic Substances Control Act (USA)
- DSL = Domestic Substances List (Canada)
- AICS = Australian Inventory of Chemical Substances

**Mixture classification according to Regulation (EC) No 1272/2008:**

- H332 Harmful if inhaled.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H334 inhaled.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated inhalative exposure.

**Classification Procedure**

- Calculation method.
- Calculation method.
- Calculation method.
- Calculation method.
- Calculation method.
- Calculation method.
- Calculation method.



**Product Name:** UPR Pole Repair™ No Flow Compound Type NF (Part A)      **Revision Date:** September 26, 2018

**Revision Number:** 7 NA

**Supersedes:** August 9, 2017

**Indication of Changes:** Section 3, 15 updated; format updates and additional California Proposition 65 information. Written in accordance with the provisions of OSHA 1910.1200 App D (2012) and Canada HPR (SOR/2015-17) (WHMIS 2015). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.

# SAFETY DATA SHEET

## 1. Identification of the substance/mixture and of the company

### 1.1 Product identifier

**Product Name:**  
**UPR Pole Repair™ No Flow**  
**UPR-NF (Part B) 10841B**

**Product ID numbers:** UPR-NFKIT4, UPR-NFKIT12, UPR-NF6B10;  
UPR-NFXXX (where XXX is the package code.)

### 1.2 Relevant identified uses of the mixture and uses advised against

**Identified uses:** Sealant, wood fill and pole repair, two-part material

**List of advices against:** Not applicable.

### 1.3 Details of the supplier of the safety data sheet

**Supplier/Manufacturer:**

**American Polywater Corporation**  
11222 - 60th Street North  
Stillwater, MN 55082 USA  
Tel: 1-651-430-2270  
Email: sds@polywater.com

### 1.4 Emergency telephone numbers

INFOTRAC: 1-800-535-5053 (USA) 1-352-323-3500 (INT'L)

## 2. Hazards Identification

### 2.1 Classification of the substance or mixture

**Classification according to USA OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).**

Skin Irritation, Cat 2; H315

Skin Sens, Cat 1, H317

Eye Irritation, Cat 2A; H319

Carc, Cat 2, H351

Target Organ Toxicity (repeated exposure), Cat 2; H373

### 2.2 Label elements

**Contains:** Diethyltoluenediamine (DETDA), 4,4'-methylenebis(2-ethylaniline), Modified Isophoronediamine



**Pictograms:**

**Signal word:** Warning

**Hazard Statements:**

- |      |   |
|------|---|
| H315 | Causes skin irritation.   |
| H317 | May cause an allergic skin reaction   |
| H319 | Causes serious eye irritation.  |
| H351 | Suspected of causing cancer   |
| H373 | May cause damage to organs through prolonged or repeated inhalative exposure. |

**Precautionary Statements:**

P264	Wash thoroughly after handling.
P280	Wear protective gloves, protective clothing and eye protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P333 + P313	If skin irritation or rash occurs: Get medical attention.
P362 + P364	Take off contaminated clothing and wash before reuse.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical attention.
P308 + P313	If exposed or concerned: Get medical attention.
P501	Dispose of contents in accordance with local regulations.

**2.3 Other hazards:** No information available.

**3. Composition/Information on Ingredients**

<b>Component</b>	<b>CAS #</b>	<b>EC #</b>	<b>Wt. %</b>
Polyether polyol mixture	Proprietary	--	60 - 100
Diethyltoluenediamine (DETDA)	68479-98-1	270-877-4	1 - 5
4,4'-methylenebis(2-ethyl-aniline)	19900-65-3	243-420-1	1 - 5
Modifiend Isophoronediamine	90530-15-7	292-053-3	1 - 5
Tertiary amine compounds	Proprietary	--	0.1 - 1

**4. First Aid Measures**

**4.1 Description of first aid measures**

- Eye Contact:** Immediately flush eyes with large quantity of water for 15 minutes. Seek medical attention.
- Skin Contact:** Remove contaminated clothing; flush skin thoroughly with soap and water. If irritation occurs, seek medical attention.
- Inhalation (Breathing):** If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention.
- Ingestion (Swallowing):** If swallowed, get medical attention. Do not induce vomiting. If patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person. Do not leave victim unattended.

**4.2 Most important symptoms and effects, both acute and delayed**

No information available.

**4.3 Indication of immediate medical attention and special treatment needed.**

No information available.

**5. Firefighting Measures**

**5.1 Extinguishing media:**

Water Fog, Carbon Dioxide, Dry Chemical or Foam.

**5.2 Special hazards arising from the substance or mixture**

**Hazardous decomposition and by-products:**

Carbon monoxide, carbon dioxide, nitrogen oxides, nitric acid, ammonia, aldehydes, nitrosamine, and silicon dioxide.

**5.3 Advice for firefighters**

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be used to cool fire exposed container to prevent pressure build-up and possible auto-ignition or rupture.

**6. Accidental Release Measures**

**6.1 Personal precautions, protective equipment and emergency procedures:**

Wear full protective clothing, including appropriate respiratory protection.

**6.2 Environmental precautions:**

Prevent from entering waterways.

**6.3 Methods materials for containment and cleaning up:**

Spills expected to be small quantities. Collect excess material with absorbents or wipe with dry towels. Wash with a dilute ammonia solution.

**6.4 Reference to other sections:**

Refer to Sections 4, 5, 8, and 13 for more information.

**7. Handling and Storage**

**7.1 Precautions for safe handling**

Use and store this product with adequate ventilation. Avoid inhalation of vapors and personal contact with the product. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Wash thoroughly after handling. Wash contaminated clothing before reuse. For industrial or professional use only.

**7.2 Conditions for safe storage, including incompatibilities**

Keep containers dry and away from excessive heat. Keep cartridges capped and sealed. Protect from freezing. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

**7.3 Specific end uses**

See technical data sheet on this product for further information.

**8. Exposure Controls / Personal Protection**

**8.1 Control parameters**

**Exposure limits and recommendations:**

Contains no components with established Occupational Exposure Limit (OEL) values.

**8.2 Exposure controls**

**Respiratory protection:**

Use with adequate ventilation to keep vapor concentration below acceptable limits.

**Protective gloves:**

The use of chemically resistant gloves is recommended to prevent skin contact. Suitable materials include neoprene, butyl rubber, Viton, Buna N, and chlorinated polyethylene.

**Eye protection:**

Safety glasses recommended.

**Other protective equipment:**

Use protective cream if skin contact is likely. Remove and wash contaminated clothing before reuse. Discard contaminated shoes.

**9. Physical and Chemical**

**9.1 Information of basic physical and chemical properties**

<b>Appearance:</b>	Light brown liquid
<b>Odor threshold:</b>	Mild amine odor
<b>pH:</b>	Not available
<b>Freezing point:</b>	Not available
<b>Boiling point:</b>	Not available
<b>Flash point:</b>	>360°F / >182°C (PMCC)
<b>Evaporation rate:</b>	Not available
<b>Flammability (solid, gas):</b>	Does not apply
<b>Upper/lower flammability or explosive limits:</b>	Not available

Vapor pressure:	Not available
Vapor density (Air = 1):	>1
Specific gravity (H <sub>2</sub> O = 1):	Not available
Solubility in water:	Slightly soluble
Partition coefficient: n-octanol/water:	Not available
Auto-ignition temperature:	Not available
Decomposition temperature:	Not available
Viscosity:	Not available

**9.2 Other Information**

Volatiles (Weight %):	0%
VOC Content:	0 g/l

**10. Stability and Reactivity**

**10.1 Reactivity:**

No dangerous reaction known under conditions of normal use.

**10.2 Chemical stability:**

Stable

**10.3 Possibility of hazardous reactions:**

Hazardous reactions will not occur under normal transport or storage conditions.

**10.4 Conditions to avoid:**

Avoid freezing, high temperatures, and moisture.

**10.5 Incompatible materials :**

Isocyanates, strong oxidizing agents and strong bases.

**10.6 Hazardous decomposition products:**

Carbon monoxide, carbon dioxide, and nitrous oxides.

**11. Toxicological Information**

**11.1 Information on toxicological effects:**

**Acute toxicity**

**Eye contact:**

Direct eye contact with material or vapors may cause eye irritation.

**Skin contact:**

May cause skin irritation

**Irritation and Sensitization Potential:**

May cause skin sensitization.

**Inhalation (Breathing):**

May cause respiratory irritation.

**Ingestion:**

Harmful if swallowed.

**Toxicity to Animals:**

Diethyltoluenediamine (DETDA):	LD <sub>50</sub> (oral rat) 738 mg/kg
	LD <sub>50</sub> (dermal rabbit) >2,000 mg/kg

**Aspiration Hazard:**

No aspiration hazard expected.

**Chronic Exposure:**

<b>Reproductive Toxicity:</b>	Not available.
<b>Mutagenicity:</b>	Not available.
<b>Teratogenicity:</b>	Not available.
<b>Specific Target Organ Toxicity (STOT)</b>	Not available.
<b>Toxicologically Synergistic Products:</b>	Not available.
<b>Carcinogenic Status:</b>	This substance has not been identified as a carcinogen or probable carcinogen by NTP, IARC, or OSHA, nor have any of its components. Contains 4,4'-methylenebis(2-ethylaniline) CAS# 19900-65-3; REACH Annex VI (EU) suspected carcinogen.

**12. Ecological Information**

<b>12.1 Aquatic Toxicity:</b>	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
<b>12.2 Persistence and degradability:</b>	No information available.
<b>12.3 Bioaccumulation potential:</b>	No information available.
<b>12.4 Mobility in soil:</b>	No information available.
<b>12.5 Results of PBT and vPvB Assessment:</b>	This product is not, nor does it contain a substance that is a PBT or vPvB.
<b>12.6 Other adverse effects:</b>	None known.

**13. Disposal Considerations**

Do not release to the environment. Dispose of product in accordance with National and Local Regulations.

**14. Transport Information**

<b>UN Number:</b>	Not Listed
<b>UN Proper shipping name:</b>	Not Applicable
<b>Transport hazard class(es):</b>	Not Applicable
<b>Packing group:</b>	Not Applicable
<b>Environmental hazards:</b>	None known
<b>Special precautions:</b>	None known
<b>TDG:</b>	Not Regulated
<b>ICAO/IATA-DGR:</b>	Not Regulated
<b>IMDG:</b>	Not Regulated
<b>ADR/RID:</b>	Not Regulated

**15. Regulatory Information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**USA Federal and State**

All components are listed on the TSCA inventory.

<b>Hazard Categories for SARA Section 311/312 Reporting</b>	<u>Acute</u>	<u>Chronic</u>	<u>Fire</u>	<u>Pressure</u>	<u>Reactive</u>
	Yes	Yes	No	No	No

This product contains diethyltoluenediamine (DETDA) (CAS 68479-98-1) which is subject to TSCA 12(b), Section 4 export notification.

**Components** CERCLA/SARA Sec 302 SARA Sec. 313  
**Hazardous Substance RQ** **EHS TPQ** **Toxic Release**  
The components of UPR Pole Repair No Flow - Part B are not affected by these Superfund regulations.

**NFPA Ratings:** Health: 2  
Fire: 1  
Reactivity: 0

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

**California Proposition 65**

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm or has been assessed to be below OEHHA Safe Harbor exposure levels required for labeling.

**European Union**

Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Contains no substance on the REACH candidate list  $\geq 0.1\%$  SCL. Does not contain notified substances from the ELINCS List, Directive 92/32/EEC. Contains no REACH substances with Annex XVII restrictions.

**Canada**

All components are listed on the DSL inventory.  
This product has been classified according to the hazard criteria of the CPR.

**Australia**

All components are listed on the AICS.

**15.2 Chemical Safety Assessment**

No chemical safety assessment has been carried out for the mixture by the supplier.

**16. Other Information**

**Abbreviations and acronyms:**

- OSHA = Occupational Safety and Health Administration
- CLP = Classification, Labeling and Packaging Regulation
- STOT = Specific Target Organ Toxicity
- LD<sub>50</sub> = Median Lethal Dose
- DNEL = Derived No Effect Level
- ACGIH = American Conference of Governmental Industrial Hygienists
- TSCA = Toxic Substances Control Act (USA)
- DSL = Domestic Substances List (Canada)
- AICS = Australian Inventory of Chemical Substances

**Mixture classification according to Regulation (EC) No 1272/2008:**

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.

**Classification Procedure**

- Calculation method.
- Calculation method.
- Calculation method.
- Calculation method.
- Calculation method.

**Revision Date:** September 26, 2018  
**Revision Number:** 6 NA  
**Supersedes:** August 16, 2017  
**Other:** Not Applicable

**Product Name:** UPR Pole Repair™ No Flow Compound Type NF (Part B)      **Revision Date:** September 26, 2018

**Indication of Changes:** Section 3, 15 updated; format updates and additional California Proposition 65 information. Written in accordance with the provisions of OSHA 1910.1200 App D (2012) and Canada HPR (SOR/2015-17) (WHMIS 2015). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.