

SAFETY DATA SHEET

1. Identification of the substance/mixture and of the company

1.1 Product identifier

**Product Name: Fiberglass Wax
Cleaner/Water Repellent**

Product ID numbers: W-16
W-XXX (Where XXX is the package code.)

1.2 Relevant identified uses of the mixture and uses advised against

Identified uses: Clean and wax preparation

List of advices against: Not applicable.

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

Polywater Europe BV
Zuidhaven 9-11 Unit B2
4761 CR Zevenbergen
Netherlands
Tel: +31 (0)10 2330578
Email: sds@polywater.com

American Polywater Corporation
11222 - 60th Street North
Stillwater, MN 55082 USA
Tel: 1-651-430-2270
Email: sds@polywater.com

Local Contact Information

1.4 Emergency telephone numbers

INFOTRAC: 1-800-535-5053 (USA) 1-352-323-3500 (INT'L)

National Poison Information Centre (NVIC): +31(0)30 274 8888
(Professional use for acute poisoning only, Netherlands.)
Local poison control information.

2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to EU Regulation (EC) No 1272/2008 and Australia WHS Regulation (2011).

Flam Liq 3	H226
Eye Irrit. 2	H319
STOT RE 1 (CNS)	H372
Aquatic Chronic 3	H412

2.2 Label elements

Contains: Distillates (petroleum), hydrotreated light, Solvent naphtha (petroleum); medium aliphatic, Poly(oxy-1,2-ethanediyl), a-uncelcyl-w-hydroxy, Fuller's Earth



Pictograms:

Signal word: Danger

Hazard Statements:

H226	Flammable liquid and vapor.
H319	Causes serious eye irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements:

Product Name: Fiberglass Wax Cleaner/Water Repellent (W-16)

Revision Date: 29 September 2016

P210 Keep away from sparks, flames and hot surfaces. No smoking.
P273 Avoid release to the environment.
P280 Wear protective gloves and eye protection.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.
P337 + P313 If eye irritation persists get medical attention.
P370 + P378 In case of fire: Use water fog, foam, dry chemical or carbon dioxide for extinction.

2.3 Other hazards: No information available.

3. Composition/Information on Ingredients

<u>Component</u>	<u>CAS #</u>	<u>EC #</u>	<u>Wt. %</u>	<u>GHS/CLP Classification</u>
Petroleum distillates, hydrotreated light	64742-47-8	265-149-8	30 – 40%	Asp. Tox. 1
Solvent naphtha (petroleum); medium aliphatic	64742-88-7	265-191-7	30 – 40%	Asp Tox 1 ; STOT RE 1 (CNS) Acute Tox 4; Eye Irrit. 2; Aquatic Acute 2
Poly(oxy-1,2-ethanediy), a-uncelcyl-w-hydroxy	34398-01-1	500-084-3	1 - 5%	Acute Tox 4; Aquatic Chronic 2
Fuller's Earth	8031-18-3	--	1 - 5%	Eye Irrit 2
Anhydrous Aluminum Silicate	66402-68-4	266-340-9	1 - 5%	Carc 1A; STOT RE 1 (resp)
Crystalline Silica	14808-60-7	238-878-4	< 0.1%	

4. First Aid Measures

4.1 Description of first aid measures

Eye Contact: If eye irritation from exposure to vapors develops, move to fresh air. Flush eyes with clean water. If irritation persists, seek medical attention. For direct eye contact, flush with large quantity of water for 15 minutes. Seek medical attention.

Skin Contact: Remove contaminated clothing; flush skin thoroughly with water. If irritation occurs, seek medical attention.

Inhalation (Breathing): If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention. If breathing is difficult, provide oxygen. If not breathing, give artificial respiration. Seek immediate medical attention.

Ingestion (Swallowing): Do not induce vomiting or give anything by mouth unless directed to do so by medical personnel. Get medical attention if symptoms appear.

4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 for more information.

4.3 Indication of immediate medical attention and special treatment needed.

No data available.

5. Firefighting Measures

5.1 Extinguishing media:

Carbon dioxide, water fog, dry chemical or foam.

5.2 Special hazards arising from the substance or mixture

Hazardous decomposition and by-products:

Burning generates carbon monoxide, carbon dioxide.

5.3 Advice for firefighters

Wear appropriate, protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Use water spray to cool fire exposed containers.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures:

Keep away from heat/sparks/open flames/hot surfaces. No smoking. For a spill in a confined space, provide mechanical ventilation to disperse or exhaust vapors. For emergency responders: use respiratory protection: half-face or full-face respirator with filter(s) for organic vapor for spills in a confined space. Chemical goggles are recommended if splashes or contact with eyes is possible. For small spills: normal antistatic work clothes are usually adequate.

6.2 Environmental precautions:

Avoid release to the environment. Dyke the spill to prevent entry into waterways, sewers, basements or confined areas.

6.3 Methods materials for containment and cleaning up:

Absorb spill with sand or absorbents. Collect as much of the spilled material as possible using non-sparking tools and transfer to a container. Seal the container. Remember, adding an absorbent material does not change the toxicity or flammability hazard.

6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

7. Handling and Storage

7.1 Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Avoid breathing vapors or spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use only outdoors or in a well-ventilated area. For industrial or professional use only.

7.2 Conditions for safe storage, including incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool.

7.3 Specific end uses

See product flyer for further information.

8. Exposure Controls / Personal Protection

8.1 Control parameters

Exposure limits and recommendations:

Petroleum Distillates, hydrotreated light

Country/Source	Long-term exposure limit – 8 hr TWA	Short-term exposure limit – 15 min
Manufacturer, RCP* TWA	1200 mg/m ³	--
Germany DFG**	350 mg/m ³ (vapor); 5 mg/m ³ (airborne particles)	700 mg/m ³ (vapor) 20 mg/m ³ (airborne particles)
USA, OSHA PEL	2000 mg/m ³ , 500 ppm (as petroleum distillates (naphtha))	--

Commented [c1]: Technically this only applies to CASRN 8002-05-9 but I think ok to use since your supplier does too

8.2 Exposure controls

Respiratory protection:

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Use a respirator or gas mask with cartridges for organic vapors (NIOSH or CE approved) with particulate pre-filter, P100 or AP2.

Protective gloves:

For repeated or prolonged skin contact, the use of impermeable gloves is recommended to prevent drying and possible irritation.

Suggested Material: Nitrile Rubber

Product Name: Fiberglass Wax Cleaner/Water Repellent (W-16)

Revision Date: 29 September 2016

Suggested Thickness: For short term contact (<15 minutes), splashes use 0.2 mm. For full contact use 0.4 mm

Exact break-through time has not been determined. Guidance is based on similar chemistry/material. Maximum wearing time should be determined based on 50 % of the penetration time determined by EN 374 part III.

Eye protection:

Safety glasses recommended.

Other protective equipment:

It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.

9. Physical and Chemical

9.1 Information of basic physical and chemical properties

Appearance:	Opaque, slightly thickened liquid.
Odor threshold:	Not available
pH:	8.9
Freezing point:	Not available
Boiling point:	> 212°F / > 100°C
Flash point:	115°F / 46°C (TCC)
Evaporation rate:	Not available
Flammability (solid, gas):	Not applicable to liquids
Flammability limits:	Not available
Vapor pressure:	Not available
Vapor density (Air = 1):	Not available
Specific gravity (H₂O = 1):	0.85
Solubility in water:	Not available
Coefficient of Water/Oil Distribution:	Not available
Auto-ignition temperature:	Not available
Decomposition temperature:	Not available
Viscosity:	Not available

9.2 Other Information

No additional information available

10. Stability and Reactivity

10.1 Reactivity:

See remaining headings in Section 10.

10.2 Chemical stability:

Stable

10.3 Possibility of hazardous reactions:

None known.

10.4 Conditions to avoid:

Avoid heat, flame, and sparks.

10.5 Incompatible materials :

Strong acids, alkalis, oxidizing agents.

10.6 Hazardous decomposition products:

Aldehydes, carbon dioxide, carbon monoxide.

11. Toxicological Information

11.1 Information on toxicological effects:

Acute toxicity

Eye contact:

Direct eye contact causes serious eye irritation.

Skin contact:

Prolonged or repeated skin exposure can remove oils, causing redness, drying and cracking. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material.

Irritation and Sensitization Potential:

Product may be irritating to skin and eyes. It is not a sensitizer.

Inhalation (Breathing):

Concentrated solvent vapors may cause irritation of the nose and throat. Prolonged exposure to excessively high vapor concentrations can result in central nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

Ingestion:

Ingestion of large quantities may cause irritation of the digestive tract, nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

Toxicity to Animals:

Calculated values: LD50 (oral rat) >2,000 mg/kg
LD50 (dermal rabbit) >2,000 mg/kg
LC50 (inhl rat) >5 mg/L

Chronic Exposure:

Reproductive Toxicity: No data available.
Mutagenicity: No data available
Teratogenicity: No data available
Specific Target Organ Toxicity (STOT): Kidneys, lungs, liver, mucous membranes, upper respiratory tract, skin, central nervous system (CNS).
Toxicologically Synergistic Products: Not available.
Carcinogenic Status: This substance has not been identified as a carcinogen or probable carcinogen by NTP, IARC, or OSHA, nor have any of its components. Silica dust is not in a respirable form.

12. Ecological Information

12.1 Toxicity:
Ecotoxicity: No information available.
Aquatic Toxicity: No information available.
12.2 Persistence and degradability: No information available
12.3 Bioaccumulation potential: No information available
12.4 Mobility in soil: No information available
12.5 Results of PBT and vPvB Assessment: This product is not, nor does it contain a substance that is a PBT or vPvB.
12.6 Other adverse effects: None known.

13. Disposal Considerations

Dispose of product in accordance with National and Local Regulations.

14. Transport Information

US DOT Domestic Ground Transportation: Type W is classified as a Combustible Liquid and is not regulated for Domestic ground transportation when shipped in non-bulk containers (< 400 liters/105.8

Product Name: Fiberglass Wax Cleaner/Water Repellent (W-16)

Revision Date: 29 September 2016

gallons per container). No special packaging, marking, labeling, and paperwork requirements apply.

ICAO/IATA-DGR: UN 1993, Flammable Liquid, N.O.S., (Contains, Petroleum Distillates), Class 3, III

IMDG: UN 1993, Flammable Liquid, N.O.S., (Contains, Petroleum Distillates), Class 3, III

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Contains no substance on the REACH candidate list $\geq 0.1\%$ SCL. Does not contain notified substances from the ELINCS List, Directive 92/32/EEC. Contains no REACH substances with Annex XVII restrictions.

Australia

All components are listed on the AICS.
Hazardous according to criteria of NOHSC Australia.

USA Federal and State

All components are listed on the TSCA inventory.

Canada

All components are listed on the DSL inventory.

15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier

16. Other Information

Abbreviations and acronyms:

OSHA = Occupational Safety and Health Administration
CLP = Classification, Labeling and Packaging Regulation
STOT = Specific Target Organ Toxicity
LD₅₀ = Median Lethal Dose
DNEL = Derived No Effect Level
ACGIH = American Conference of Governmental Industrial Hygienists
TSCA = Toxic Substances Control Act (USA)
DSL = Domestic Substances List (Canada)
AICS = Australian Inventory of Chemical Substances

Mixture classification according to Regulation (EC) No 1272/2008:

H226	Flammable liquid and vapor.
H319	Causes serious eye irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Classification Procedure

Calculation method.
Calculation method.
Calculation method.
Calculation method.

Revision Date: 29 September 2016

Revision Number: 4

Supersedes: 2 January 2015

Other: Not Applicable

Indication of Changes: Section 1, 2, 3, 8, 15, 16 updated. Hazard evaluation, updated exposure information. Written in accordance with the provisions of REACH Annex II (EU No 453/2010) and Australia WHS Regulation (2011). (GHS format)

Product Name: Fiberglass Wax Cleaner/Water Repellent (W-16)

Revision Date: 29 September 2016

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.