

SAFETY DATA SHEET

1. Identification of the substance/mixture and of the company

1.1 Product identifier

**Product Name: Fiberglass Wax
Cleaner/Water Repellent**

Product ID numbers: W-16
W-XXX (Where XXX is the package code.)

1.2 Relevant identified uses of the mixture and uses advised against

Identified uses: Clean and wax preparation

List of advices against: Not applicable.

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

American Polywater Corporation

11222 - 60th Street North

Stillwater, MN 55082 USA

Tel: 1-651-430-2270

Email: sds@polywater.com

1.4 Emergency telephone numbers

INFOTRAC: 1-800-535-5053 (USA) 1-352-323-3500 (INT'L)

2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to USA OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).

Flam Liq 3 H226

Eye Irrit. 2A H319

STOT RE 1 (kidneys, lungs, liver, mucous
membranes, upper respiratory tract, skin CNS) H372

2.2 Label elements

Contains: Distillates (petroleum), hydrotreated light, Solvent naphtha (petroleum); medium aliphatic, Poly(oxy-1,2-ethanediyl), a-uncelcyl-w-hydroxy



Pictograms:

Signal word: Danger

Hazard Statements:

H226 Flammable liquid and vapor.
H319 Causes serious eye irritation.
H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements:

P210 Keep away from sparks, flames and hot surfaces. No smoking.
P233 Keep container tightly closed.
P242 Use only non-sparking tools.
P260 Do not breathe vapor.

P264	Wash thoroughly after handling.
P280	Wear eye protection.
P303 + P361 + P353	IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.
P337 + P313	If eye irritation persists get medical attention.
P370 + P378	In case of fire: Use water fog, foam, dry chemical or carbon dioxide for extinction.
P403 + P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local and national regulations.

2.3 Other hazards: No information available.

3. Composition/Information on Ingredients

<u>Component</u>	<u>CAS #</u>	<u>EC #</u>	<u>Wt. %</u>	<u>GHS/CLP Classification</u>
Distillates (petroleum), hydrotreated light	64742-47-8	265-149-8	30 – 40%	Asp Tox 1, H304
Solvent naphtha (petroleum); medium aliphatic	64742-88-7	265-191-7	30 – 40%	Asp Tox 1, H304; STOT RE 1; H372
Poly(oxy-1,2-ethanediyl), a-uncelcyl-w-hydroxy	34398-01-1	500-084-3	1 - 5%	Acute Tox 4, H302; Eye Irrit. 2, H319 --
Oleic Acid	112-80-1	204-007-1	1 - 5%	--
Fuller's Earth	8031-18-3	--	1 - 5%	--
Anhydrous Aluminum Silicate	66402-68-4	266-340-9	1 - 5%	--
Crystalline Silica	14808-60-7	238-878-4	< 0.11%	--

4. First Aid Measures

4.1 Description of first aid measures

- Eye Contact:** If eye irritation from exposure to vapors develops, move to fresh air. Flush eyes with clean water. If irritation persists, seek medical attention. For direct eye contact, flush with large quantity of water for 15 minutes. Seek medical attention.
- Skin Contact:** Remove contaminated clothing; flush skin thoroughly with water. If irritation occurs, seek medical attention.
- Inhalation (Breathing):** If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention. If breathing is difficult, provide oxygen. If not breathing, give artificial respiration. Seek immediate medical attention.
- Ingestion (Swallowing):** Do not induce vomiting or give anything by mouth unless directed to do so by medical personnel. Get medical attention if symptoms appear.

4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 for more information.

4.3 Indication of immediate medical attention and special treatment needed.

No data available.

5. Firefighting Measures

5.1 Extinguishing media:

Carbon dioxide, water fog, dry chemical or foam.

5.2 Special hazards arising from the substance or mixture

Hazardous decomposition and by-products:

Burning generates carbon monoxide, carbon dioxide.

5.3 Advice for firefighters

Wear appropriate, protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Use water spray to cool fire exposed containers.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures:

Keep away from heat/sparks/open flames/hot surfaces. No smoking. For a spill in a confined space, provide mechanical ventilation to disperse or exhaust vapors. For emergency responders: use respiratory protection: half-face or full-face respirator with filter(s) for organic vapor for spills in a confined space. Chemical goggles are recommended if splashes or contact with eyes is possible. For small spills: normal antistatic work clothes are usually adequate.

6.2 Environmental precautions:

Avoid release to the environment. Dyke the spill to prevent entry into waterways, sewers, basements or confined areas.

6.3 Methods materials for containment and cleaning up:

Absorb spill with sand or absorbents. Collect as much of the spilled material as possible using non-sparking tools and transfer to a container. Seal the container. Remember, adding an absorbent material does not change the toxicity or flammability hazard.

6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

7. Handling and Storage

7.1 Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Avoid breathing vapors or spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use only outdoors or in a well-ventilated area. For industrial or professional use only.

7.2 Conditions for safe storage, including incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool.

7.3 Specific end uses

See product flyer for further information.

8. Exposure Controls / Personal Protection

8.1 Control parameters

Exposure limits and recommendations:

Petroleum distillates, hydrotreated light (64742-47-8); Solvent naphtha, medium aliphatic (64742-88-7)

Country/Source	Long-term exposure limit – 8 hr TWA	Short-term exposure limit – 15 min
USA, OSHA PEL	2000 mg/m ³ , 500 ppm (as petroleum distillates (naphtha))	--
Manufacturer, RCP* TWA Alberta, Quebec, Yukon, British Columbia,	1200 mg/m ³	--
Saskatchewan, Ontario*	Not established	Not established

* Manitoba, Newfoundland and Labrador, Nova Scotia, and Prince Edward Island are all based on the current ACGIH TLVs. New Brunswick is based on an older version ACGIH. Nunavet and Northwest Territories are based heavily on current ACGIH TLVs.

8.2 Exposure controls

Respiratory protection:

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Use a respirator or gas mask with cartridges for organic vapors (NIOSH-approved) or use supplied air equipment.

Protective gloves:

For repeated or prolonged skin contact, the use of impermeable gloves is recommended to prevent drying and possible irritation.

Suggested Material: Nitrile Rubber

Suggested Thickness: For short term contact (<15 minutes), splashes use 0.2 mm. For full contact use 0.4 mm

Exact break-through time has not been determined. Guidance is based on similar chemistry/material.

Maximum wearing time should be determined based on 50 % of the penetration time determined by EN 374 part III.

Eye protection:

Safety glasses recommended.

Other protective equipment:

It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.

9. Physical and Chemical

9.1 Information of basic physical and chemical properties

Appearance:	Opaque, slightly thickened liquid.
Odor threshold:	Not available
pH:	8.9
Freezing point:	Not available
Boiling point:	> 212°F / > 100°C
Flash point:	115°F / 46°C (TCC)
Evaporation rate:	Not available
Flammability (solid, gas):	Not applicable to liquids
Flammability limits:	Not available
Vapor pressure:	Not available
Vapor density (Air = 1):	Not available
Specific gravity (H₂O = 1):	0.85
Solubility in water:	Not available
Coefficient of Water/Oil Distribution:	Not available
Auto-ignition temperature:	Not available
Decomposition temperature:	Not available
Viscosity:	Not available

9.2 Other Information

No additional information available

10. Stability and Reactivity

10.1 Reactivity:

See remaining headings in Section 10.

10.2 Chemical stability:

Stable

10.3 Possibility of hazardous reactions:

None known.

10.4 Conditions to avoid:

Avoid heat, flame, and sparks.

10.5 Incompatible materials :

Strong acids, alkalis, oxidizing agents.

10.6 Hazardous decomposition products:

Aldehydes, carbon dioxide, carbon monoxide.

11. Toxicological Information

11.1 Information on toxicological effects:

Acute toxicity

Eye contact:

Direct eye contact causes serious eye irritation.

Skin contact:

Prolonged or repeated skin exposure can remove oils, causing redness, drying and cracking. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material.

Irritation and Sensitization Potential:

Product may be irritating to skin and eyes. It is not a sensitizer.

Inhalation (Breathing):

Concentrated solvent vapors may cause irritation of the nose and throat. Prolonged exposure to excessively high vapor concentrations can result in central nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

Ingestion:

Ingestion of large quantities may cause irritation of the digestive tract, nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

Toxicity to Animals:

Calculated values: LD₅₀ (oral rat) >2,000 mg/kg
 LD₅₀ (dermal rabbit) >2,000 mg/kg
 LC₅₀ (inhl rat) >5 mg/L

Chronic Exposure:

Reproductive Toxicity: No data available.

Mutagenicity: No data available

Teratogenicity: No data available

Specific Target Organ Toxicity (STOT) Kidneys, lungs, liver, mucous membranes, upper respiratory tract, skin, central nervous system (CNS).

Toxicologically Synergistic Products: Not available.

Carcinogenic Status: This substance has not been identified as a carcinogen or probable carcinogen by NTP, IARC, or OSHA, nor have any of its components. Silica dust is not in a respirable form.

12. Ecological Information

12.1 Toxicity:

Ecotoxicity: No information available.

Aquatic Toxicity: No information available.

12.2 Persistence and degradability: No information available

12.3 Bioaccumulation potential: No information available

12.4 Mobility in soil: No information available

12.5 Results of PBT and vPvB Assessment: This product is not, nor does it contain a substance that is a PBT or vPvB.

12.6 Other adverse effects: None known.

13. Disposal Considerations

Dispose of product in accordance with National and Local Regulations.

14. Transport Information

US DOT Domestic Ground Transportation:	Type W is classified as a Combustible Liquid and is not regulated for Domestic ground transportation when shipped in non-bulk containers (< 400 liters/105.8 gallons per container). No special packaging, marking, labeling, and paperwork requirements apply.
ICAO/IATA-DGR:	UN 1993, Flammable Liquid, N.O.S., (Contains, Petroleum Distillates), Class 3, III
IMDG:	UN 1993, Flammable Liquid, N.O.S., (Contains, Petroleum Distillates), Class 3, III

15. Regulatory Information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****USA Federal and State**

All components are listed on the TSCA inventory.

Hazard Categories for SARA Section 311/312 Reporting	<u>Acute</u> Yes	<u>Chronic</u> Yes	<u>Fire</u> No	<u>Pressure</u> No	<u>Reactive</u> No
---	---------------------	-----------------------	-------------------	-----------------------	-----------------------

Components	CERCLA/SARA Sec 302 Hazardous Substance RQ	EHS TPQ	SARA Sec. 313 Toxic Release
Components are not affected by these Superfund regulations.			

NFPA Ratings:	Health:	2
	Fire:	2
	Reactivity:	0

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

European Union

Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Contains no substance on the REACH candidate list $\geq 0.1\%$ SCL. Does not contain notified substances from the ELINCS List, Directive 92/32/EEC. Contains no REACH substances with Annex XVII restrictions.

Canada

All components are listed on the DSL inventory.
This product has been classified according to the hazard criteria of the CPR.

Australia

All components are listed on the AICS.
Hazardous according to criteria of NOHSC Australia.

15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier

16. Other Information**Abbreviations and acronyms:**

OSHA = Occupational Safety and Health Administration
CLP = Classification, Labeling and Packaging Regulation
STOT = Specific Target Organ Toxicity
LD₅₀ = Median Lethal Dose
DNEL = Derived No Effect Level
ACGIH = American Conference of Governmental Industrial Hygienists
TSCA = Toxic Substances Control Act (USA)
DSL = Domestic Substances List (Canada)
AICS = Australian Inventory of Chemical Substances

Mixture classification according to Regulation (EC) No 1272/2008:

H226 Flammable liquid and vapor.
H319 Causes serious eye irritation.
H372 Causes damage to organs through prolonged or repeated exposure.

Classification Procedure

Physical Testing
Calculation method.
Calculation method.

Revision Date: August 4, 2017
Revision Number: 4 NA
Supersedes: January 2, 2015
Other: Not Applicable
Indication of Changes: Section 1, 2, 8, 16 updated. Included North American classification and exposure information.
Written in accordance with the provisions of OSHA 1910.1200 App D (2012) and Canada HPR (SOR/2015-17)(WHMIS 2015). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.