

MATERIAL SAFETY DATA SHEET

1. IDENTIFICATION OF MATERIAL AND SUPPLIER

ADAPT Australia Pty. Ltd.

11 - 19 Global Drive
Tullamarine Victoria 3043
Telephone Number. 03 9330 0666

**Product Name: AirRepair® -
Leak Sealant Paste Hardener –
Part B Single-Use Package**

Emergency Telephone Number: 1 800 039 008

Chemical Description: Sealant Hardener
Product Use: Sealing Leaks

2. HAZARDS IDENTIFICATION

Not classified as hazardous according to criteria of NOHSC Australia

Risk Phrases: Not Applicable

Safety Phrases: Not Applicable

NFPA Ratings: Health: 1
Fire: 1
Reactivity: 0

3. COMPOSITION / INFORMATION ON INGREDIENTS

<u>Components</u>	<u>CAS #</u>	<u>Weight %</u>
Polymercaptan Curing Agent	Proprietary	30 - 50
2,4,6-Tris (Dimethylaminomethyl) Phenol	90-72-2	<5

4. FIRST AID MEASURES

Eye Contact: If eye irritation from exposure to vapors develops, move to fresh air. Flush eyes with clean water. If irritation persists, seek medical attention. For direct eye contact, flush with large quantity of water for 15 minutes. Seek medical attention.

Skin Contact: Remove contaminated clothing; flush skin thoroughly with water. If irritation continues, seek medical attention.

Inhalation (Breathing): If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention.

Ingestion (Swallowing): Drink one or two glasses of milk or water. Do not induce vomiting. If victim is unconscious, place on the left side with head down. Never give anything by mouth to an unconscious person. Do not leave victim unattended. Seek medical attention.

5. FIRE-FIGHTING MEASURES

Flash Point: >200°C (PMCC)
Flammable Limits: Not Available
Autoignition Temperature: Not Available
Hazardous Decomposition Products: Oxides of carbon, oxides of sulfur, oxides of nitrogen.
Extinguishing Media: Water Fog, Carbon Dioxide, Dry Chemical or Foam

Special Precautions:	Full protective equipment including self-contained breathing apparatus should be used. Water spray may be used to cool fire-exposed container to prevent pressure build-up and possible auto-ignition or rupture.
Unusual Hazards:	Toxic smoke and vapors may form during combustion.

6. ACCIDENTAL RELEASE MEASURES

Major spill unlikely with small package. Residual resin may be removed using steam or hot soapy water. Dispose of according to local and federal regulations. Prevent spill from entering drainage/sewer systems, waterways, and surface waters.

7. HANDLING AND STORAGE

Avoid contact with skin, eyes, or clothing. Uncured AirRepair™ Leak Sealant Paste, Part B is a skin irritant. Use good personal hygiene practice. Provide appropriate ventilation/respiratory protection against decomposition products during welding/flame operations (i.e. torches used to install heat shrink products) on or near cured product. Keep containers cool, dry, and away from sources of ignition. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory Protection:	None required with proper ventilation.
Protective Gloves:	The use of impervious gloves is recommended to prevent skin contact.
Eye Protection:	Eye protection is recommended especially if the material is used in ways where it could contact the eyes.
Other Protective Equipment:	Use protective cream if skin contact is likely. Remove and wash contaminated clothing before reuse. Discard contaminated shoes.
Exposure Limits and Recommendations:	TLV values for components have not been determined by OSHA, ACGIH, nor Worksafe Australia Exposure Standards.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	White to yellow paste; unpleasant, slight sulfur, pungent odor
Odor Threshold:	Not Available
Vapor Density (Air = 1):	Not Available
Specific Gravity (H₂O = 1):	<2.0
Solubility in Water:	Negligible
Boiling Point:	Not Applicable
Freezing Point:	Not Applicable
Vapor Pressure:	<< 1 mm Hg @ 20°C
Coefficient of Water/Oil Distribution:	Not Available
pH:	Not Applicable
Volatiles (Weight %):	0%

10. STABILITY AND REACTIVITY

Stability:	Stable
Conditions to Avoid:	Open flame and extreme heat.
Materials to Avoid:	Strong oxidizing agents.
Hazardous Decomposition Products:	Oxides of carbon, oxides of sulfur, oxides of nitrogen.
Conditions Under Which Hazardous Polymerization May Occur:	When Sealant Resin (Part A) is mixed with Sealant Hardener (Part B), heat is generated. Use caution if combining and mixing more than one single-use package.

11. TOXICOLOGICAL INFORMATION

Eye Contact:	Direct eye contact with material or vapors may cause severe eye irritation.
Skin Contact:	May cause severe skin irritation, especially on prolonged contact.
Irritation and Sensitization Potential:	Prolonged or repeated skin exposure may cause skin sensitization.
Inhalation (Breathing):	Excess vapor exposure may cause irritation of the nose and throat. Prolonged exposure may cause delayed lung injury and chemical pneumonia.
Ingestion (Swallowing):	Ingestion may cause irritation of the gastrointestinal tract, nausea, vomiting, and diarrhea.
Oral Toxicity:	Material is considered slightly toxic.
Chronic Exposure:	Not Available.
Carcinogenic Status:	This substance has not been identified as a carcinogen or probable carcinogen by NTP, IARC, or OSHA, nor have any of its components.
Reproductive Toxicity:	Not Available
Mutagenicity:	Not Available
Teratogenicity:	Not Available
Toxicologically Synergistic Products:	Not Available

12. ECOLOGICAL INFORMATION

Ecotoxicity:	No information available.
Persistence and Degradability:	No information available.
Mobility:	No information available.
Bioaccumulation:	No information available.
Other:	

13. DISPOSAL CONSIDERATIONS

Dispose of product in accordance with National and Local Regulations.

14. TRANSPORTATION INFORMATION

UN Number:	Not Listed
UN Proper Shipping Name:	Not Applicable
Class and Subsidiary Risk:	Not Applicable
Packing Group:	Not Applicable

15. REGULATORY INFORMATION

All components are listed on the AICS.

16. OTHER INFORMATION

Date Reviewed: 23 May 2006
Reviewed By: S. H. Dahlke

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.