

Section 1. Identification

Product identifier

Product Identity HydraSol® Cable Gel Remover Saturated Wipe or Towel Package

Other means of identification HS-1, HS-1C, HS-1M, HS-1D42, HS-D72, HS-D72C

Relevant identified uses of the substance or mixture and uses advised against

See Technical Data Sheet.

Details of the supplier of the safety data sheet

Company Name American Polywater Corporation
11222 - 60th Street North
Stillwater, MN 55082 USA

Emergency
24 hour Emergency Telephone No. INFOTRAC: 1-800-535-5053 (USA)
1-352-323-3500 (INT'L)

Customer Service: Tel: 1-651-430-2270
Email: sds@polywater.com

Section 2. Hazard(s) identification

Classification of the substance or mixture under US OSHA's Hazard Communication Standard (1910.1200) revised 2024 and Canadian Hazardous Products Regulations (SOR/2015-17) (GHS revision 7)

Flammable Liquid 4;H227	Combustible Liquid.
Skin corrosion/irritation category 2;H315	Causes skin irritation.
Serious eye damage / eye irritation, category 2A;H319	Causes serious eye irritation.
Skin sensitizer category 1;H317	May cause an allergic skin reaction.

Label elements



Warning

H227 Combustible liquid.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

[Prevention]

P210 Keep away from heat, sparks, open flames, and other ignition sources - No smoking.
P260 Do not breathe dust, fume, mist, vapors or spray.
P261 Avoid breathing dust, fume, gas, mist, vapors, spray.
P262 Do not get in eyes, on skin, or on clothing.
P264 Wash thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves, eye protection, and face protection.

[Response]

P301+310 IF SWALLOWED: Immediately call a POISON CENTER, doctor or physician.
P302+352 IF ON SKIN: Wash with plenty of soap and water.
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331 Do NOT induce vomiting.
P333+313 If skin irritation or a rash occurs: Get medical advice or attention.
P337+313 If eye irritation persists: Get medical advice or attention.
P362+364 Take off contaminated clothing and wash it before reuse.
P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.
P391 Collect spillage.

[Storage]

P403+235 Store in a well ventilated place. Keep cool.

[Disposal]

P501 Dispose of contents or container in accordance with local and national regulations.

Other hazards

This product contains no PBT/vPvB/vPvM chemicals.

This product contains no endocrine disrupting chemicals.

Does not contain component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS) per the Organisation for Economic Co-operation and Development (OECD) list of Per- and Polyfluoroalkyl Substances (PFASs).

Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of US OSHA's Hazard Communication Standard (1910.1200) revised 2024 and Canadian Hazardous Products Regulations (SOR/2015-17) (GHS revision 7)

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Hydrocarbon Solvent CAS Number: 64742-48-9 Synonyms: Hydrotreated heavy naphtha (petroleum), Naphtha (petroleum), hydrotreated heavy	10 - 30	Aspiration hazard, category 1;H304	-----
Citrus Terpenes CAS Number: 5989-27-5 Synonyms: (R)-p-mentha-1,8-diene, Cyclohexene, 1-methyl-4-(1-methylethenyl)-, (R)-, D-Limonene	10 - 30	Flammable Liquid, category 3;H226 Skin corrosion/irritation category 2;H315 Skin sensitizer category 1;H317 Aquatic toxicity (acute), category 1;H400 Aquatic toxicity (chronic), category 1;H410 Aspiration hazard, category 1;H304	-----
Sorbitan monooleate CAS Number: 1338-43-8 Synonyms: Sorbitan oleate	1 - 5	Not Classified	-----
Alcohols, C12-15, ethoxylated CAS Number: 68131-39-5 Synonyms: Ethoxylated Alcohols	0.5 - 1.5	Serious eye damage / eye irritation, category 1;H318 Aquatic toxicity (acute), category 1;H400 Acute toxicity(oral), category 4;H302	-----

The actual concentration or concentration range is withheld as a trade secret.

*PBT/vPvB - PBT, vPvM or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

Description of first aid measures

- General** In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
- Eyes** Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
- Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
- Ingestion** If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Overview POTENTIAL HEALTH EFFECTS

Eye Contact: May cause tearing, stinging, redness, irritation, and burns.

Inhalation: Irritating to respiratory tract. Prolonged or repeated breathing of very high vapor concentrations cause euphoria, excitation, and dizziness, headaches, nausea, and vomiting, abdominal pain, fatigue, muscular weakness. Aspiration into the lungs can cause CNS (central nervous system) and subsequent aspiration into the lungs can cause pulmonary edema and chemical pneumonia depression. Chronic overexposure in high concentrations may produce CNS depression.

Ingestion: Irritation of the mouth, esophagus, and stomach can develop following ingestion. Symptoms include burning of the mouth, sore throat, vomiting, nausea, dizziness, loss of consciousness. Due to its light viscosity, there is danger of aspiration into the lungs during vomiting. Aspiration can result in severe lung damage or death.

Skin Contact: Prolonged or repeated skin contact may cause moderate to severe irritation including itching and redness of the skin, defatting, and/or dermatitis. This product can also be absorbed through the skin and produce CNS symptoms. Single prolonged exposure is not likely to result in the product being absorbed through the skin in harmful amounts.

Signs And Symptoms Of Exposure: Eye irritation, respiratory irritation, drying and cracking of skin, dizziness, fatigue, headache, unconsciousness or asphyxiation. Chronic effects of ingestion and subsequent aspiration into the lungs can cause pneumatocele (lung cavity) formation and chronic lung dysfunction. Repeated breathing of vapors can cause effects to liver and kidneys.

Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may

result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Eyes Causes serious eye irritation.

Skin May cause an allergic skin reaction. Causes skin irritation.

Section 5. Fire-fighting measures

Extinguishing media

Use dry chemicals, carbon dioxide foam, water fog, or inert gas (nitrogen) for small fires. For large fires use foam, water fog, or water spray. Water fog and spray are effective in cooling containers and adjacent structures but might cause frothing and/or not achieve extinguishment. A water jet may be used to cool the container's external walls to prevent pressure build-up, auto ignition, or explosion. NEVER use a water jet directly on the fire. Product will float and can be re-ignited on surface of water.

Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

Do not breathe dust, fume, mist, vapors or spray.

Avoid breathing dust, fume, gas, mist, vapors, spray.

Do not get in eyes, on skin, or on clothing.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

ERG Guide No.

128

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).
Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8.
Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.
Eliminate ignition sources. Soak up with noncombustible absorbent material. Remove absorbent material for proper disposal.

Section 7. Handling and storage

Precautions for safe handling

Handle containers carefully to prevent damage and spillage.
Store in accordance with the National Fire Protection Association's publication NFPA 30, Flammable and Combustible Liquids Code. 29 CFR 1910.106 applies to the handling, storage, and use of flammable and combustible liquids.
See section 2 for further details. - [Prevention]

Conditions for safe storage, including any incompatibilities

Store in a cool dry area, away from heat, sparks and open flame.
Keep containers sealed when not in use.
Store out of direct sunlight.

Incompatible materials: Strong acids, alkalis, and oxidizers such as liquid chlorine, halogens, hydrogen peroxide, oxygen.

Other Precautions: All labeled precautions must be observed when handling, storing and transporting empty containers due to product residues. Do not reuse containers. Empty containers may contain material residues which can ignite with explosive force. Cutting or welding of empty containers can cause fire, explosion, or release fumes from residues. Keep containers closed and drum bungs in place. Dispose of in a licensed facility.

See section 2 for further details. - [Storage]

Specific end use(s)

No available information

Section 8. Exposure controls / personal protection

Control parameters

Exposure Limits

CAS No.	Ingredient	Source	Value
1338-43-8	Sorbitan monooleate	ACGIH	No Established Limit
		OSHA	No Established Limit
		NIOSH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit
5989-27-5	Citrus Terpenes	ACGIH	No Established Limit
		OSHA	No Established Limit
		NIOSH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit

Safety Data Sheet
HydraSol® Cable Gel Remover
Saturated Wipe or Towel Package

Revision Date:
14 October, 2025

CAS No.	Ingredient	Source	Value
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit
64742-48-9	Hydrocarbon Solvent	ACGIH	No Established Limit
		OSHA	No Established Limit
		NIOSH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit
68131-39-5	Alcohols, C12-15, ethoxylated	ACGIH	No Established Limit
		OSHA	No Established Limit
		NIOSH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit

Exposure

controls

Respiratory If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes Protective safety glasses recommended

Skin Avoid skin contact. Wear nitrile or similar chemical resistant gloves to keep skin contact to a minimum.

Refer to the manufacturer's recommendations regarding the suitability of any gloves used.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any

vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

Information on basic physical and chemical properties

Physical State	Liquid
Color	Milky white emulsion solution
Odor	Citrus
Odor threshold	No available information
Melting point / freezing point	No available information
Initial boiling point and boiling range	212°F (100°C) Initial
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: No available information Upper Explosive Limit: No available information
Flash Point	155°F (68°C), Closed Cup (PMCC)
Auto-ignition temperature	No available information
Decomposition temperature	No available information
pH	7.0
Viscosity	No available information
Solubility in Water	No available information
Partition coefficient n-octanol/water (Log Kow)	No available information
Vapor pressure (Pa)	10.5 mm Hg @ 20°C
Relative Density	0.91
Vapor Density	No available information
Evaporation rate (Ether = 1)	<0.06 (n-butyl acetate = 1)
VOC Content	375 g/l
Oxidising properties	No available information
Explosive properties	No available information
% Volatile	>97%

Other information

No other relevant information.

Section 10. Stability and reactivity

Reactivity

Hazardous Polymerization will not occur.

Chemical stability

Stable under normal circumstances.

Possibility of hazardous reactions

No available information

Conditions to avoid

Excessive heat and open flame.

Incompatible materials

Strong acids, alkalis, and oxidizers such as liquid chlorine, halogens, hydrogen peroxide, oxygen.

Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Safety Data Sheet
HydraSol® Cable Gel Remover
Saturated Wipe or Towel Package

Revision Date:
14 October, 2025

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Hydrocarbon Solvent - (64742-48-9)	> 5,000.00, Rat - Category: NA	>2,000.00, Rabbit - Category: 5	No data available.	No data available.	No data available.
Citrus Terpenes - (5989-27-5)	>2,000.00, Rat - Category: 5	> 5,000.00, Rabbit - Category: NA	No data available.	No data available.	No data available.
Sorbitan monooleate - (1338-43-8)	No data available.	No data available.	No data available.	No data available.	No data available.
Alcohols, C12-15, ethoxylated - (68131-39-5)	> 5,000.00, Rat - Category: NA	>2,000.00, Rat - Category: 5	No data available.	No data available.	No data available.

Carcinogen Data

CAS No.	Ingredient	Source	Value
1338-43-8	Sorbitan monooleate	IARC	No
		ACGIH	No Established Limit
5989-27-5	Citrus Terpenes	IARC	Group 3
		ACGIH	No Established Limit
64742-48-9	Hydrocarbon Solvent	IARC	No
		ACGIH	No Established Limit
68131-39-5	Alcohols, C12-15, ethoxylated	IARC	No
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation	2A	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	1	May cause an allergic skin reaction.
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable

Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

Possible routes of entry:

Inhalation, ingestion, skin contact, and skin absorption.

Symptoms and effects, both acute and delayed:

POTENTIAL HEALTH EFFECTS

Eye Contact: May cause tearing, stinging, redness, irritation, and burns.

Inhalation: Irritating to respiratory tract. Prolonged or repeated breathing of very high vapor concentrations cause euphoria, excitation, and dizziness, headaches, nausea, and vomiting, abdominal pain, fatigue, muscular weakness. Aspiration into the lungs can cause CNS (central nervous system) and subsequent aspiration into the lungs can cause pulmonary edema and chemical pneumonia depression. Chronic overexposure in high concentrations may produce CNS depression.

Ingestion: Irritation of the mouth, esophagus, and stomach can develop following ingestion. Symptoms include burning of the mouth, sore throat, vomiting, nausea, dizziness, loss of consciousness. Due to its light viscosity, there is danger of aspiration into the lungs during vomiting. Aspiration can result in severe lung damage or death.

Skin Contact: Prolonged or repeated skin contact may cause moderate to severe irritation including itching and redness of the skin, defatting, and/or dermatitis. This product can also be absorbed through the skin and produce CNS symptoms. Single prolonged exposure is not likely to result in the product being absorbed through the skin in harmful amounts.

Signs And Symptoms Of Exposure: Eye irritation, respiratory irritation, drying and cracking of skin, dizziness, fatigue, headache, unconsciousness or asphyxiation. Chronic effects of ingestion and subsequent aspiration into the lungs can cause pneumatocele (lung cavity) formation and chronic lung dysfunction. Repeated breathing of vapors can cause effects to liver and kidneys.

Treat symptomatically.

Eyes Causes serious eye irritation.

Skin May cause an allergic skin reaction. Causes skin irritation.

Section 12. Ecological information

Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Hydrocarbon Solvent - (64742-48-9)	18.00, Oncorhynchus mykiss	4.50, Daphnia magna	3.10, Pseudokirchneriella subcapitata
Citrus Terpenes - (5989-27-5)	0.72, Pimephales promelas	0.31, Daphnia magna	0.32, Pseudokirchneriella subcapitata
Sorbitan monooleate - (1338-43-8)	No data available.	No data available.	No data available.
Alcohols, C12-15, ethoxylated - (68131-39-5)	3.10, Scophthalmus maximus	0.23, Daphnia magna	3.20, Skeletonema costatum

Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

No available information

Mobility in soil

No available information

Results of PBT and vPvB assessment

This product contains no PBT/vPvB/vPvM chemicals.

Other adverse effects

No available information

Section 13. Disposal considerations

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.

Section 14. Transport information

Not regulated for packages under 5L (1.3 gallons) or 5.0 kg (11 lbs).

Classification Method: Classified as per Part 2, Sections 2.1-2.8 of the Transportation of Dangerous Goods Regulations.

DOT (Domestic Surface Transportation)

UN number	NA1993
UN proper shipping name	Combustible liquid, n.o.s., (CHEMICAL NAME)
Transport hazard class(es)	Combustible liquid
Sub Class	Not Applicable
Packing group	III

TDG (Domestic Surface Transportation)

UN number	Not Regulated
UN proper shipping name	Not Regulated
Transport hazard class(es)	Combustible liquid
Sub Class	Not Applicable
Packing group	Not Applicable

IMO / IMDG (Ocean Transportation)

UN number	Not Regulated
UN proper shipping name	Not Regulated
Transport hazard class(es)	Not Applicable
Sub Class	Not Applicable
Packing group	Not Applicable

ICAO/IATA

UN number	Not Regulated
UN proper shipping name	Not Regulated
Transport hazard class(es)	Not Applicable
Sub Class	Not Applicable
Packing group	Not Applicable

Environmental hazards

IMDG Marine Pollutant: Yes; (Citrus Terpenes)

Special precautions for user

No available information

Section 15. Regulatory information

**Regulatory
Overview**

The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

This product has been classified in accordance with US OSHA's Hazard Communication Standard (1910.1200) revised 2024 and Canadian Hazardous Products Regulations (SOR/2015-17 amended 2022-12-15) (GHS revision 7) and the SDS contains all of the information required by those regulations.

All components of this material are either listed or exempt from listing on the TSCA Inventory.

All components of this material are either listed or exempt from listing on the DSL or NDSL Inventories.

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):

Benzene

Cumene

Ethylbenzene

Naphthalene

Proposition 65 - Developmental Toxins (>0.0%):

Benzene

Toluene

Proposition 65 - Female Repro Toxins (>0.0%):

Toluene

Proposition 65 - Male Repro Toxins (>0.0%):

Benzene

Proposition 65 Label Warning:



WARNING: This product can expose you to chemicals including [Benzene, Cumene, Ethylbenzene , Naphthalene], which are known to the State of California to cause cancer, and [Benzene, Toluene], which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Section 16. Other information

Revision Date

14 October, 2025

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

End of Document