PolywaterPedFloor™

PEDESTAL SEALING FOAM BARRIER



Safeguard enclosures and equipment to prevent costly unplanned outages or service disruptions



FEATURES AND BENEFITS

• PREVENTS

Keeps mice, rats, snakes, insects, and water from entering the pedestal or cabinet

PROTECTS

Cured product offers permanent protection through weather extremes

• EASY TO USE

Ready to mix and apply—No water needed

THOROUGH SEAL

Flows and self-levels before expansion to seal the entire opening, including complex shapes

RE-ENTERABLE

Allows for the installation of new ducts or cables after being installed

Safeguard Enclosures and Equipment from Damage

Polywater® PedFloor™ creates a hard foam ground barrier that improves service reliability and safety by keeping out moisture and blocking pests from burrowing into enclosures. Polywater PedFloor thoroughly adheres to various pedestal and conduit materials to make a permanent seal, yet can be re-enterable if needing to install new ducts.



CATALOG #	PACKAGE DESCRIPTION	UNITS/CASE
PF-1	Kit Includes: PedFloor Burst Pack 750 ml, Plastic Sheet, Roll Duct Tape, Gloves, and Instruction Sheet Covers ~1 sq ft (0.09 m2), 3" (7.6 cm) thick	2
PF-2	Kit Includes: PedFloor Burst Pack 1500 ml, Plastic Sheet, Duct Tape Roll, Gloves, and Instruction Sheet Covers ~2 sq ft (0.19 m2), 3" (7.6 cm) thick	2
PF-3	Kit Includes: (1) Bottle Part A, (1) Bottle Part B, Mixing Pail, Plastic Sheet, Mixing Stick, Duct Tape Roll, Gloves, Instruction Sheet Covers ~0.28 m2 (3 sq ft), 7.6 cm (3") Thick	1



SPECIFICATIONS AND APPLICATIONS

- **Strong:** Structural, cross-linked matrix creates a sturdy seal with a tensile strength of 101 psi.
- Field-ready Kits: Polywater PedFloor Foam Pedestal Sealant is supplied in kits that contain all accessories needed to create a strong protective barrier. The kits include resins, plastic containment sheet, tape, gloves, and instructions. The PF-1 and PF-3 contain premeasured containers of the two-part foam. The PF-2 and FSTBP-200B6 are "burst packs" in which the parts A & B are mixed in the flexible package after breaking the center seal of the pack.
- For More Information, View the Technical Data Sheet

polywater.com | +1 651-430-2270

IMPORTANT NOTICE: The statements here are made in good faith based on tests and observations we believe to be reliable, However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for anyloss, injury, or direct, indirect, or consequential damages resulting from a product's use, regardless of the legal theory asserted.



American Polywater Corporation 11222 60th Street N. Stillwater, MN 55082 USA

+1 651-430-2270 Main +31 10 233 0578 Europe, Middle East, N. Africa email: support@polywater.com