

Polywater® Pad N Pole™

UTILITY ENCLOSURE REPAIR SYSTEM



For Field Repair of Utility Enclosures, Poles, and Pedestals

Finished Pad N Pole repair

PRODUCT BENEFITS

- **Protects:** Seals defects from unwanted entry.
- **Prevents:** Helps stop outages and costly changeouts.
- **Durable:** Withstands environmental extremes. Sunlight (UV) resistant.
- **Versatile:** Repairs damage of various shapes and sizes.
- **Easy to Use:** Kit contains materials to complete repair in a single visit,

Restores System Integrity

Polywater® Pad N Pole™ (BRK™) fixes and restores damaged utility enclosures to prevent human, water, and pest intrusion. Polywater Pad N Pole two-part adhesive bonds to fiberglass, steel, polyethylene, metal, concrete, and composites. The resin repair system provides a durable, long-lasting repair.



Clean and sand before applying BRK



Wet the fabric with BRK

polywater.com | 651-430-2270

American
Polywater
Corporation

ADHESIVES | CLEANERS | LUBRICANTS | SEALANTS



Kit components



Painted BRK repair

Multi-Use Cartridge Creates Numerous Repairs

Polywater Pad N Pole Repair is supplied in kits that contain everything needed to perform multiple repairs. A standard high-ratio caulking gun can be used to dispense product.

POLYWATER PAD N POLE

Catalog #	Package Description	Units/Case
BRK-250KIT1	1 - 250mL Pad N Pole Repair adhesive cartridge; 6 - mixing nozzles; 1 - strip of sanding cloth; 6 - Type HP™ wet/dry wipes (cat #HP-P158ID); 6 - pairs of gloves; 6 - foam brushes; 1 - 72" x 6" fabric; 1 - instruction sheet. Dispensing tool not included.	1
BRK-250KITB6	Contains 6 BRK-250KIT1	1
TOOL-250	Dispensing tool	1
MXR-18S-10	10-pack of mixing nozzles for BRK units/case	1

SPECIFICATIONS AND APPLICATIONS:

- Pad N Pole is perfect for repairing electrical enclosures, transformer pads, fiberglass light poles, PVC and fiberglass conduit, and riser poles. The material in the kits can be custom cut to cover and mold to various types of damage.
- Pad N Pole fixes a wide variety of defects, from small cracks to large holes. Multiple layers can be applied for increased strength over large areas.
- Pad N Pole Repair is quick and easy to install. Pad N Pole mixed resin has 30 minutes working time. It can be painted immediately after application, eliminating the need for a return visit. Repairs reach full strength in 12 hours.
- Repairs made with Pad N Pole Repair withstand exposure to extreme outdoor temperatures, from -60°F to 180°F.

CONTACT US

1-800-328-9384 Toll Free

1-651-430-2270 Main

1-651-430-3634 Fax

email: support@polywater.com

IMPORTANT NOTICE: The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct, indirect, or consequential damages resulting from product's use, regardless of the legal theory asserted.

American
Polywater[®]
Corporation

11222 60th Street N | Stillwater, MN 55082 USA