

# SAFETY DATA SHEET

## 1. Identification of the substance/mixture and of the company

### 1.1 Product identifier

**Product Name:**  
**Type EFW™ Isopropanol Wipe**

Product ID numbers: EFW-1,

### 1.2 Relevant identified uses of the mixture and uses advised against

Identified uses: Preparation wipe for PE fusion.

List of advices against: Not applicable.

### 1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

**American Polywater Corporation**

11222 - 60th Street North

Stillwater, MN 55082 USA

Tel: 1-651-430-2270

Email: sds@polywater.com

### 1.4 Emergency telephone numbers

INFOTRAC: 1-800-535-5053 (USA) 1-352-323-3500 (INT'L)

## 2. Hazards Identification

### 2.1 Classification of the substance or mixture

Classification according to USA OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).

Flam Liq 2 H225

Eye Irrit. 2 H319

STOT SE 3 H336

### 2.2 Label elements

Contains: Isopropanol



Pictograms:

Signal word: Danger

Hazard Statements:

H225 Highly flammable liquid and vapor

H319 Causes serious eye irritation

H336 May cause drowsiness or dizziness

Precautionary Statements:

P210 Keep away from sparks, flames and hot surfaces. No smoking.

P261 Avoid breathing vapor.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

- P338 if present and easy to do. Continue rinsing.
- P337 + P313 If eye irritation persists: Get medical attention.
- P370 + P378 In case of fire: Use water fog, foam, dry chemical or carbon dioxide for extinction.
- P403 + P235 Store in a well-ventilated place. Keep cool.
- P501 Dispose of contents according to local regulations.

**2.3 Other hazards:** No information available.

### 3. Composition/Information on Ingredients

<u>Component</u>	<u>CAS #</u>	<u>EC #</u>	<u>Wt. %</u>
Isopropanol	67-63-0	200-661-7	100

### 4. First Aid Measures

#### 4.1 Description of first aid measures

- Eye Contact:** If eye irritation from exposure to vapors develops, move to fresh air. Flush eyes with clean water. If irritation persists, seek medical attention. For direct eye contact, flush with large quantity of water for 15 minutes. Seek medical attention.
- Skin Contact:** Remove contaminated clothing; flush skin thoroughly with water. If irritation occurs, seek medical attention.
- Inhalation (Breathing):** If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention. If breathing is difficult, provide oxygen. If not breathing, give artificial respiration. Seek immediate medical attention.
- Ingestion (Swallowing):** Do not induce vomiting or give anything by mouth unless directed to do so by medical personnel. Get medical attention if symptoms appear.

#### 4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 for more information.

#### 4.3 Indication of immediate medical attention and special treatment needed.

Causes serious eye irritation.

### 5. Firefighting Measures

#### 5.1 Extinguishing media:

Carbon dioxide, water fog, dry chemical or foam.

#### 5.2 Special hazards arising from the substance or mixture

##### Hazardous decomposition and by-products:

Burning generates carbon monoxide, carbon dioxide.

#### 5.3 Advice for firefighters

Wear appropriate, protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Use water spray to cool fire exposed containers.

### 6. Accidental Release Measures

#### 6.1 Personal precautions, protective equipment and emergency procedures:

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Limited spill hazard with saturated towel package. For small spills: normal antistatic work clothes are usually adequate.

#### 6.2 Environmental precautions:

Avoid release to the environment.

#### 6.3 Methods materials for containment and cleaning up:

Collect towel and absorb any excess material with sand or absorbents.

#### 6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

**7. Handling and Storage**

**7.1 Precautions for safe handling**

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Avoid breathing vapors or spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use only outdoors or in a well-ventilated area. For industrial or professional use only.

**7.2 Conditions for safe storage, including incompatibilities**

Store in a well-ventilated place. Keep cool. Store away from acids and oxidizing agents.

**7.3 Specific end uses**

See technical data sheet on this product for further information.

**8. Exposure Controls / Personal Protection**

**8.1 Control parameters**

**Exposure limits and recommendations:**

**Isopropanol, 2-propanol (67-63-0)**

Country/Source	Long-term exposure limit – 8 hr. TWA	Short-term exposure limit – 15 min
USA, OSHA NIOSH	980 mg/m <sup>3</sup> , 400 ppm	1,225 mg/m <sup>3</sup> , 500 ppm
USA, ACGIH	200 ppm	400 ppm
British Columbia	200 ppm	400 ppm
Alberta	492 mg/m <sup>3</sup> , 200 ppm	984 mg/m <sup>3</sup> , 400 ppm
Quebec	985 mg/m <sup>3</sup> , 400 ppm	1,230 mg/m <sup>3</sup> , 500 ppm
Saskatchewan*	200 ppm	400 ppm

\* Manitoba, Newfoundland and Labrador, Nova Scotia, and Prince Edward Island are all based on the current ACGIH TLVs. New Brunswick is based on an older version ACGIH. Nunavut and Northwest Territories are based heavily on current ACGIH TLVs.

**8.2 Exposure controls**

**Respiratory protection:**

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Use a respirator or gas mask with cartridges for organic vapors (NIOSH-approved) or use supplied air equipment.

**Protective gloves:**

For repeated or prolonged skin contact, the use of impermeable gloves is recommended to prevent drying and possible irritation.

Suggested Material: Nitrile Rubber

Suggested Thickness: For short term contact (<15 minutes), splashes use 0.2 mm. For full contact use 0.4 mm

Nitrile, minimum 0.38 mm thickness or comparable protective barrier material with a high performance level for continuous contact use conditions, permeation breakthrough minimum 480 minutes in accordance with CEN standards EN 420 and EN 374.

**Eye protection:**

Safety glasses recommended.

**Other protective equipment:**

It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.

**9. Physical and Chemical**

**9.1 Information of basic physical and chemical properties (bulk liquid)**

**Appearance:** Clear, colorless liquid; typical alcohol odor.

<b>Odor threshold:</b>	22 ppm
<b>pH:</b>	Does not apply
<b>Freezing point:</b>	-130°F / -90°C
<b>Boiling point:</b>	180°F / 82°C
<b>Flash point:</b>	55°F / 13°C (TCC)
<b>Evaporation rate:</b>	1.7 (n-butyl acetate = 1)
<b>Flammability (solid, gas):</b>	Not applicable to liquids
<b>Upper/lower flammability or explosive limits:</b>	<b>LEL:</b> 2% <b>UEL:</b> 12.7%
<b>Vapor pressure:</b>	4.4 kPa @20°C
<b>Vapor density (Air = 1):</b>	2.07 (Air = 1)
<b>Specific gravity (H<sub>2</sub>O = 1):</b>	0.79
<b>Solubility in water:</b>	Complete
<b>Coefficient of Water/Oil Distribution:</b>	0.1 This product is equally soluble in oil and water.
<b>Auto-ignition temperature:</b>	Not available
<b>Decomposition temperature:</b>	Not available
<b>Viscosity:</b>	Not available

**9.2 Other Information**

<b>Volatiles (Weight %):</b>	100%
<b>VOC Content:</b>	790 g/l

**10. Stability and Reactivity**

**10.1 Reactivity:**

See remaining headings in Section 10.

**10.2 Chemical stability:**

Stable

**10.3 Possibility of hazardous reactions:**

None known.

**10.4 Conditions to avoid:**

Avoid heat, flame, and sparks.

**10.5 Incompatible materials :**

Strong oxidizing agents.

**10.6 Hazardous decomposition products:**

Carbon dioxide, carbon monoxide.

**11. Toxicological Information**

**11.1 Information on toxicological effects:**

**Acute toxicity**

**Eye contact:**

Direct eye contact may cause eye irritation. This irritation is minimal and expected to be transient.

**Skin contact:**

Prolonged or repeated skin exposure can remove oils, causing redness, drying and cracking. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material.

**Irritation and Sensitization Potential:**

Product may be irritating to skin and eyes. It is not a sensitizer.



ICAO/IATA-DGR: Not Regulated (See Special Provision A46)

IMDG: Not Regulated (See Special Provision 216)

**15. Regulatory Information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**USA Federal and State**

All components are listed on the TSCA inventory.

<b>Hazard Categories for SARA Section 311/312 Reporting</b>	<u>Acute</u> Yes	<u>Chronic</u> No	<u>Fire</u> Yes	<u>Pressure</u> No	<u>Reactive</u> No
---	---------------------	----------------------	--------------------	-----------------------	-----------------------

<b>Components</b>	<b>CERCLA/SARA Sec 302 Hazardous Substance RQ</b>	<b>EHS TPQ</b>	<b>SARA Sec. 313 Toxic Release</b>
-------------------	---	----------------	--

Components are not affected by these Superfund regulations.

<b>NFPA Ratings:</b>	Health:	1
	Fire:	3
	Reactivity:	0

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

**California Proposition 65**

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm or has been assessed to be below OEHHA Safe Harbor exposure levels required for labeling.

**European Union**

Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Contains no substance on the REACH candidate list  $\geq$  0.1% SCL. Does not contain notified substances from the ELINCS List, Directive 92/32/EEC. Contains no REACH substances with Annex XVII restrictions.

**Canada**

All components are listed on the DSL inventory.

This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

**Australia**

All components are listed on the AICS.

Hazardous according to criteria of NOHSC Australia.

**15.2 Chemical Safety Assessment**

No chemical safety assessment has been carried out for the mixture by the supplier.

**16. Other Information**

**Abbreviations and acronyms:**

- OSHA = Occupational Safety and Health Administration
- CLP = Classification, Labeling and Packaging Regulation
- STOT = Specific Target Organ Toxicity
- LD<sub>50</sub> = Median Lethal Dose
- DNEL = Derived No Effect Level
- ACGIH = American Conference of Governmental Industrial Hygienists
- TSCA = Toxic Substances Control Act (USA)
- DSL = Domestic Substances List (Canada)
- AICS = Australian Inventory of Chemical Substances

**Revision Date:** September 20, 2018  
**Revision Number:** 3  
**Supersedes:** August 7, 2017  
**Other:** Not Applicable  
**Indication of Changes:** Section 3, 15 updated; format updates and additional California Proposition 65 information. Written in accordance with the provisions of OSHA 1910.1200 App D (2012) and Canada HPR (SOR/2015-17) (WHMIS 2015). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.