

# Polywater®

## Dyna-Blue®



THICK WATER-BASED GEL LUBRICANT



## The Best Cable Lubricant Choice for Manual Application

Polywater® Dyna-Blue® thick, gel cable lubricant is clean, dries slippery, and will not separate out during freeze thaw cycles. It has a high cling factor for easy handling and application. It is compatible with common electrical cables. A good choice for everyday use when installing building wire, such as THHN, XHHW, and fire alarm cables.



### FEATURES AND BENEFITS

- **NON-STAINING**  
Will not stain clothing, carpet, or sheetrock
- **HIGH CLING FACTOR**  
Stays on wires during vertical application
- **TEMPERATURE STABLE**  
Not ruined by freeze/thaw exposure
- **WIPES CLEAN AND DRY**  
Wire markers stick to cable jackets
- **UL/ULC LISTED**  
UL Listed to US and Canadian safety standards

# Polywater® Dyna-Blue®



CATALOG #	PACKAGE DESCRIPTION	UNITS/CASE
D-35	1 qt (0.95 L) Bottle	12
D-128	1 gal (3.8 L) Pail	4
D-640	5 gal (18.9 L) Pail	1
D-DRUM	55 gal (208 L) Drum	1



EMT, GRS, or IMC applications.

## SPECIFICATIONS AND APPLICATIONS

- **Cable Compatibility:** Passes IEEE 1210 physical and electrical testing on a wide variety of cable materials. It does not stress crack polyethylene. UL and ULC listed.
- **Physical Properties:** Dries slippery. Unlike wax lubes, it leaves little residue and will not cement cables to conduit. Contains no wax, grease, or silicone.
- **Temperature Use Range:** 20°F to 120°F (-5°C to 50°C).
- **Temperature Stability:** No phase-out after five freeze/thaw cycles or 5-day exposure at 120°F (50°C).

[polywater.com](http://polywater.com) | +1 651-430-2270

IMPORTANT NOTICE: The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct, indirect, or consequential damages resulting from a product's use, regardless of the legal theory asserted.

© 2022 American Polywater Corporation LIT-DYNABUEFLYER/REV000

**Polywater**<sup>®</sup>  
Solutions at work.

American Polywater Corporation  
11222 60th Street N.  
Stillwater, MN 55082 USA

+1 651-430-2270 Main  
+31 10 233 0578 Europe, Middle East, N. Africa  
email: [support@polywater.com](mailto:support@polywater.com)