Polywater Type KC[™]



CONTACT CLEANER



Fast-Acting and Precise for Cleaning Around Energized Electrical Enclosures, Apparatus and Sensitive Electronics

Polywater[®] Type KC[™] effectively cleans contacts, breakers, controls, switches, substation relays, busbars, meters, traffic control electronics, cables, and circuit boards. Polywater Type KC has low VOCs (volatile organic compounds) and contains no ozone-depleting chemicals. It is safer to use in confined spaces compared to chlorinated solvents.



KC-16

- NO RESIDUE **Evaporates completely**
- NONCONDUCTIVE Will not short across typical electrical voltages once evaporated
- NO FLASH POINT Safe and nonflammable
- COMPATIBLE Suitable to use on most types of plastic, metal, and rubber
 - SAFE **Replaces chlorinated** electrical cleaners

Polywater[®] Type KC[™]



| CATALOG # | PACKAGE DESCRIPTION | UNITS/CASE | |
|---|----------------------------|------------|--|
| KC-16^{\dagger} | 16 oz (475 ml) Aerosol Can | 12 | |
| [†] Not available in Europe and Middle East. | | | |



SPECIFICATIONS AND APPLICATIONS

- **Dielectric Strength:** >25kV at a 100-mil gap per ASTM D877 standard test method.
- Flash Point: None per ASTM D93 standard test method.
- **Residue:** <100 ppm per ASTM D2369 standard test method. Leaves no residue.



© 2022 American Polywater Corporation LIT-TYPEKCFLYER/REV001

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to

indirect, or consequential damages resulting from a product's use, regardless of the legal theory asserted.

be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct,

+1 651-430-2270 Main +31 10 233 0578 Europe, Middle East, N. Africa email: support@polywater.com