

# SAFETY DATA SHEET

## 1. Identification of the substance/mixture and of the company

### 1.1 Product identifier

**Product Name:**  
**PowerPatch® Putty Stick (EP-STICK)**

**Product ID numbers:** EP-STICK4;  
Contained in EP-KITXXX (Where XXX is the package code.)

### 1.2 Relevant identified uses of the mixture and uses advised against

**Identified uses:** 2-Part Putty Sealant for temporary repair

**List of advices against:** Not applicable.

### 1.3 Details of the supplier of the safety data sheet

#### Supplier/Manufacturer:

**American Polywater Corporation**  
11222 - 60th Street North  
Stillwater, MN 55082 USA  
Tel: 1-651-430-2270  
Email: sds@polywater.com

**Powerhouse Electric Limited**  
289 Rosebank Road,  
Avondale, Auckland 1026, NZ  
09 373 4487

### 1.4 Emergency telephone numbers

INFOTRAC: 1-800-535-5053 (USA) 1-352-323-3500 (INT'L)

NPC (National Poison Centre) 0800 764 766 and 0800 Poison

## 2. Hazards Identification

### 2.1 Classification of the substance or mixture

Classification according to USA OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).

Skin Irrit 2	H315
Skin Sens 1	H317
Eye Irrit 2B	H319
Aquatic Chronic 2	H411

### 2.2 Label elements

#### Contains

Bisphenol A-epichlorohydrin polymer



#### Pictograms:

GHS07

GHS09

**Signal word:** Warning

#### Hazard Statements:

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

#### Precautionary Statements:

P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves, protective clothing and eye protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P333 + P313	If skin irritation or rash occurs: Get medical attention.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical attention.
P362 + P364	Take off contaminated clothing.
P391	Collect spillage.
P501	Dispose of container in accordance with local regulations

**2.3 Other hazards:** No information available.

**3. Composition/Information on Ingredients**

<b>Component</b>	<b>Product identifier</b>	<b>Weight %</b>	<b>Classification according to Regulation (EC) No. 1272/2008 [CLP]</b>
Bisphenol A-epichlorohydrin polymer	(CAS-No.) 25068-38-6 (EC-No.) 500-033-5 (EC Index-No.) 603-074-00-8	75 – 90	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411

This product contains no other reportable hazardous components under OSHA 29 CFR 1910, 1200 Canada and European Regulation (EC) No 1272/2008. No additional ingredients require reporting based on applicable concentration and current supplier knowledge.

**4. First Aid Measures**

**4.1 Description of first aid measures**

- Eye Contact:** Immediately flush eyes with large quantity of water for 15 minutes. Seek medical attention.
- Skin Contact:** Remove contaminated clothing; flush skin thoroughly with soap and water for at least 15 minutes. If irritation or allergic reaction occurs, seek medical attention.
- Inhalation (Breathing):** If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention.
- Ingestion (Swallowing):** No emergency medical treatment necessary

**4.2 Most important symptoms and effects, both acute and delayed**

Refer to Section 11 for more information.

**4.3 Indication of immediate medical attention and special treatment needed.**

No information available.

**5. Firefighting Measures**

**5.1 Extinguishing media:**

Water fog or fine spray, dry chemical carbon dioxide, or foam.

**5.2 Special hazards arising from the substance or mixture**

Dense smoke is emitted when burned without sufficient oxygen.

**Hazardous decomposition and by-products:**

CO<sub>2</sub>, CO, phenolics. May contain other combustion products of varying composition which may be toxic or irritating.

**5.3 Advice for firefighters**

Wear full protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Water fog may be used to cool fire exposed container to prevent pressure build-up and possible auto-ignition or rupture. Direct water stream may spread fire.

## 6. Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures:

Isolate area. Use appropriate safety equipment.

### 6.2 Environmental precautions:

Avoid release to the environment. Prevent spill from entering drainage/sewer systems, waterways, basements or confined areas. Refer to Section 12 for more information.

### 6.3 Methods materials for containment and cleaning up:

Absorb spill with sand or absorbents. Residual resin may be removed using steam or hot soapy water. Collect as much of the spilled material as possible using non-sparking tools and transfer to a container. Seal the container. Residual material can be removed with solvent.

### 6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

## 7. Handling and Storage

### 7.1 Precautions for safe handling

Avoid personal contact with the product. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Wash thoroughly after handling. Wash contaminated clothing before reuse. For industrial or professional use only.

### 7.2 Conditions for safe storage, including incompatibilities

Keep containers cool, dry, and away from sources of ignition. Keep containers and cartridges capped and sealed. Protect from freezing. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

### 7.3 Specific end uses

See technical data sheet on this product for further information.

## 8. Exposure Controls / Personal Protection

### 8.1 Control parameters

#### Exposure limits and recommendations:

Contains no components with established Occupational Exposure Limit (OEL) values.

A Derived No Effect Level (DNEL) of 12.25 mg/m<sup>3</sup> has been established for Acute Inhalation.

### 8.2 Exposure controls

#### Respiratory protection:

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced. Use a respirator or gas mask with cartridges for organic vapors (NIOSH or CE approved) with particulate pre-filter, P100 or AP2.

#### Protective gloves:

The use of chemically resistant gloves is recommended to prevent skin contact. Suitable materials include nitrile (included in most kits), neoprene, ethyl vinyl alcohol (EVAL), PVC. Use a glove with a protection class of 1 or higher (breakthrough time greater than 10 minutes according to EN 374). NOTE: The selection of specific glove for the application should account for other chemicals in the environment, physical requirements and potential user reaction to the glove material.

#### Eye protection:

Safety glasses recommended.

#### Other protective equipment:

Use protective cream if skin contact is likely. Remove and wash contaminated clothing before reuse. Discard contaminated shoes.

#### Personal protective equipment symbol(s):



## 9. Physical and Chemical

### 9.1 Information of basic physical and chemical properties

<b>Appearance:</b>	Gray/dark gray, solid putty stick. Pungent, sulfurous odor.
<b>Odor threshold:</b>	Not available
<b>pH:</b>	Not available
<b>Freezing point:</b>	Not available
<b>Boiling point:</b>	Not available
<b>Flash point:</b>	>199.9°F / >93.3°C (PMCC)
<b>Evaporation rate:</b>	Not available
<b>Flammability (solid, gas):</b>	Not available
<b>Upper/lower flammability or explosive limits:</b>	Not available
<b>Vapor pressure:</b>	Not available
<b>Vapor density (Air = 1):</b>	Not available
<b>Specific gravity (H<sub>2</sub>O = 1):</b>	2.247
<b>Solubility in water:</b>	Not available
<b>Partition coefficient: n-octanol/water:</b>	Not available
<b>Auto-ignition temperature:</b>	Not available
<b>Decomposition temperature:</b>	>392°F / >200°C
<b>Viscosity:</b>	Not available (thick putty)

### 9.2 Other Information

<b>Volatiles (Weight %):</b>	<0.1%
<b>VOC Content:</b>	0 g/l

## 10. Stability and Reactivity

### 10.1 Reactivity:

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability:

Stable

### 10.3 Possibility of hazardous reactions:

Hazardous reactions will not occur under normal transport or storage conditions.

### 10.4 Conditions to avoid:

Avoid high temperatures above 300 °C (572 °F). Decomposition can occur above 350 °C (662 °F).  
Generation of gas during decomposition can cause pressure to build in closed systems.

### 10.5 Incompatible materials :

Strong acids or bases (especially primary or secondary aliphatic amines), strong oxidizing agents.

### 10.6 Hazardous decomposition products:

CO<sub>2</sub>, CO, phenolics and other organic substances may be formed during combustion or elevated temperature degradation.

**11. Toxicological Information**

**11.1 Information on toxicological effects:**

**Acute toxicity**

**Eye contact:**

Direct eye contact with material or vapors may cause eye irritation.

**Skin contact:**

This product has moderate skin irritation potential. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material. Prolonged or repeated skin exposure may cause skin sensitization.

**Irritation and Sensitization Potential:**

May cause allergic skin reaction.

**Inhalation (Breathing):**

Low vapor pressure makes this route of exposure unlikely.

**Ingestion:**

Ingestion may cause irritation of the gastrointestinal tract.

**Toxicity to Animals:**

Bisphenol A Diglycidyl Ether: LD<sub>50</sub> (oral rat) >15,000 mg/kg  
 LD<sub>50</sub> (dermal rabbit) 23,000 mg/kg

**Aspiration Hazard:**

No aspiration hazard expected.

**Chronic Exposure:**

**Reproductive Toxicity:**

Not available.

**Mutagenicity:**

Resins based on diglycidyl ether of bisphenol A have proved to be inactive when tested by in-vivo mutagenicity assays. These resins have shown activity in in-vitro microbial mutagenicity screening and have produced chromosomal aberrations in cultured rat-liver cells. The significance of these tests to humans is unknown.

**Teratogenicity:**

Not available.

**Specific Target Organ**

**Toxicity (STOT)**

Not available.

**Toxicologically Synergistic Products:**

Not available.

**Carcinogenic Status:**

This substance has not been identified as a carcinogen or probable carcinogen by NTP, IARC, or OSHA, nor have any of its components.

**12. Ecological Information**

**12.1 Toxicity:**

**Aquatic Toxicity:**

May be toxic to aquatic organisms.

Bisphenol A Diglycidyl Ether:

LC<sub>50</sub> (96 hr.): 2 mg/l Oncorhynchus mykiss (rainbow trout)  
 Semi-static test

Bisphenol A Diglycidyl Ether:

EC<sub>50</sub> (48 hr.): 1.8 mg/l Daphnia magna (invertebrate)  
 Static test

Bisphenol A Diglycidyl Ether:

ErC<sub>50</sub> (72 hr.): 11 mg/l Fresh water algae (aquatic plants)  
 Static test

Bisphenol A Diglycidyl Ether:

Chronic Toxicity Value:  
 Daphnia magna (invertebrate), 21 d, number of offspring, NOEC: 0.3 mg/l  
 Semi-static test

**12.2 Persistence and degradability:**

Based on stringent OECD test guidelines, this material cannot be considered readily biodegradable. Biodegradability depends on environmental conditions.

Bisphenol A Diglycidyl Ether:

OECD Biodegradation Test 302B  
 12% Biodegradation, 28 d exposure

Bisphenol A Diglycidyl Ether: Theoretical Oxygen Demand  
2.35 mg/mg

**12.3 Bioaccumulation potential:**

Bioconcentration potential is moderate.

**12.4 Mobility in soil:**

Potential for mobility in soil is low..

**12.5 Results of PBT and vPvB Assessment:**

This product is not, nor does it contain a substance that is a PBT or vPvB.

**12.6 Other adverse effects:**

None known.

**13. Disposal Considerations**

Do not dump into sewer, on ground or into any body of water. Dispose of product in accordance with National and Local Regulations.

**14. Transport Information**

**DOT:** Not Regulated  
**UN Number:** 3077  
**UN Proper Shipping Name:** Environmentally hazardous substance, solid, N.O.S. (Bisphenol A)  
**Class and Subsidiary Risk:** 9  
**Packing Group:** III  
**ICAO/IATA-DGR:** Not Regulated (See Special Provision A197)  
**IMDG:** Not Regulated (See IMDG Code 2.10.2.7)  
**ADR/RID:** 9  
**Other information** For surface shipments within the United States: Not regulated.

**15. Regulatory Information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**15.1.1. NZ-Regulations**

All chemical substances in this product are listed in the New Zealand Inventory of Chemicals (NZIoC) or are exempt

This substance is to be managed using the conditions specified in an applicable Group Standard

**HSR Number**

HSR002544 Construction Products Group Standard

**15.1.2. EU-regulations**

- Contains no REACH substances with Annex XVII restrictions
- Contains no substance on the REACH candidate list
- Contains no REACH Annex XIV substances
- Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.
- Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants.

**15.1.3. Australian-regulations**

All components are listed on the AICS.

Product is classified as hazardous according to criteria of NOHSC Australia.

**15.1.4. International-regulations**

All chemical substances in this product are listed as “Active” in the US EPA (Environmental Protection Agency) “TSCA Inventory Notification (Active-Inactive) Requirements Rule” (“the Final Rule”). as of Feb. 2019 or are otherwise exempt.

### 15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier.

## 16. Other Information

### Abbreviations and acronyms:

OSHA = Occupational Safety and Health Administration

CLP = Classification, Labeling and Packaging Regulation

STOT = Specific Target Organ Toxicity

LD<sub>50</sub> = Median Lethal Dose

DNEL = Derived No Effect Level

ACGIH = American Conference of Governmental Industrial Hygienists

TSCA = Toxic Substances Control Act (USA)

DSL = Domestic Substances List (Canada)

AICS = Australian Inventory of Chemical Substances

**Revision Date:** March 14, 2022  
**Revision Number:** 9 NZ  
**Supersedes:** January 15, 2021  
**Other:** New Zealand  
**Indication of Changes:** No changes.

Written in accordance with the provisions of OSHA 1910.1200 App D (2012) and Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 including New Zealand specific information. (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.