

# SAFETY DATA SHEET

## 1. Identification of the substance/mixture and of the company

### 1.1 Product identifier

**Product Name:**  
**Type FO™ Fiber Optic Cleaner/Degreaser**

**Product ID numbers:** FO-XXX (Where XXX is the package code.)

### 1.2 Relevant identified uses of the mixture and uses advised against

**Identified uses:** Fiber and precision cleaning

**List of advices against:** Not applicable.

### 1.3 Details of the supplier of the safety data sheet

#### Supplier/Manufacturer:

**American Polywater Corporation**  
11222 - 60th Street North  
Stillwater, MN 55082 USA  
Tel: 1-651-430-2270  
Email: sds@polywater.com

**Powerhouse Electric Limited**  
289 Rosebank Road,  
Avondale, Auckland 1026, NZ  
09 373 4487

### 1.4 Emergency telephone numbers

INFOTRAC: 1-800-535-5053 (USA) 1-352-323-3500 (INT'L)  
NPC (National Poison Centre) 0800 764 766 and 0800 Poison

## 2. Hazards Identification

### 2.1 Classification of the substance or mixture

Classification according to USA OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).

Flam Liq 2	H225
Eye Irrit. 2A	H319
STOT SE 3	H336

### 2.2 Label elements

**Contains:** Isopropanol



#### Pictograms:

GHS07

GHS02

**Signal word:** Danger

#### Hazard Statements:

H225	Highly flammable liquid and vapor
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

#### Precautionary Statements:

P210	Keep away from sparks, flames and hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground, bond container and receiving equipment.

- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing vapor.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303 + P361 + P353 IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water.
- P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305 + +P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337 + P313 If eye irritation persists: Get medical attention.
- P370 + P378 In case of fire: Use water fog, foam, dry chemical or carbon dioxide for extinction.
- P403 + P235 Store in a well-ventilated place. Keep cool.
- P501 Dispose of contents/container in accordance with local and national regulations.

**2.3 Other hazards:** No information available.

**3. Composition/Information on Ingredients**

<u>Component</u>	<u>CAS #</u>	<u>EC #</u>	<u>Wt. %</u>
Isopropanol	67-63-0	200-661-7	100

**4. First Aid Measures**

**4.1 Description of first aid measures**

- Eye Contact:** If eye irritation from exposure to vapors develops, move to fresh air. Flush eyes with clean water. If irritation persists, seek medical attention. For direct eye contact, flush with large quantity of water for 15 minutes. Seek medical attention.
- Skin Contact:** Remove contaminated clothing; flush skin thoroughly with water. If irritation occurs, seek medical attention.
- Inhalation (Breathing):** If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention. If breathing is difficult, provide oxygen. If not breathing, give artificial respiration. Seek immediate medical attention.
- Ingestion (Swallowing):** Do not induce vomiting or give anything by mouth unless directed to do so by medical personnel. Get medical attention if symptoms appear.

**4.2 Most important symptoms and effects, both acute and delayed**

Refer to Section 11 for more information.

**4.3 Indication of immediate medical attention and special treatment needed.**

Causes serious eye irritation.

**5. Firefighting Measures**

**5.1 Extinguishing media:**

Carbon dioxide, water fog, dry chemical or foam.

**5.2 Special hazards arising from the substance or mixture**

**Hazardous decomposition and by-products:**

Burning generates carbon monoxide, carbon dioxide.

**5.3 Advice for firefighters**

Wear appropriate, protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Use water spray to cool fire exposed containers.

**6. Accidental Release Measures**

**6.1 Personal precautions, protective equipment and emergency procedures:**

Keep away from heat/sparks/open flames/hot surfaces. No smoking. For a spill in a confined space, provide mechanical ventilation to disperse or exhaust vapors. For emergency responders: use respiratory protection: half-face or full-face respirator with filter(s) for organic vapor for spills in a confined space. Chemical goggles are recommended if splashes or contact with eyes is possible. For small spills: normal antistatic work clothes are usually adequate.

**6.2 Environmental precautions:**

Avoid release to the environment. Dyke the spill to prevent entry into waterways, sewers, basements or confined areas.

**6.3 Methods materials for containment and cleaning up:**

Absorb spill with sand or absorbents. Collect as much of the spilled material as possible using non-sparking tools and transfer to a container. Seal the container. Remember, adding an absorbent material does not change the toxicity or flammability hazard.

**6.4 Reference to other sections:**

Refer to Sections 4, 5, 8, and 13 for more information.

**7. Handling and Storage**

**7.1 Precautions for safe handling**

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Avoid breathing vapors or spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use only outdoors or in a well-ventilated area. For industrial or professional use only.

**7.2 Conditions for safe storage, including incompatibilities**

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store away from acids and oxidizing agents.

**7.3 Specific end uses**

See technical data sheet on this product for further information.

**8. Exposure Controls / Personal Protection**

**8.1 Control parameters**

**Exposure limits and recommendations:**

**Isopropanol, 2-propanol (67-63-0)**

Country/Source	Long-term exposure limit – 8 hr. TWA	Short-term exposure limit – 15 min
WKS-15 (New Zealand Workplace Standards)	983 mg/m <sup>3</sup> , 400 ppm	1,230 mg/m <sup>3</sup> , 500 ppm
USA, OSHA NIOSH	980 mg/m <sup>3</sup> , 400 ppm	1,225 mg/m <sup>3</sup> , 500 ppm
USA, ACGIH	200 ppm	400 ppm

**8.2 Exposure controls**

**Respiratory protection:**

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Use a respirator or gas mask with cartridges for organic vapors (NIOSH-approved) or use supplied air equipment.

**Protective gloves:**

For repeated or prolonged skin contact, the use of impermeable gloves is recommended to prevent drying and possible irritation.

Suggested Material: Nitrile Rubber

Suggested Thickness: For short term contact (<15 minutes), splashes use 0.2 mm. For full contact use 0.4 mm

Nitrile, minimum 0.38 mm thickness or comparable protective barrier material with a high performance level for continuous contact use conditions, permeation breakthrough minimum 480 minutes in accordance with CEN standards EN 420 and EN 374.

**Eye protection:**

Safety glasses recommended.

**Other protective equipment:**

It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.

**9. Physical and Chemical**

**9.1 Information of basic physical and chemical properties**

<b>Appearance:</b>	Clear, colorless liquid; typical alcohol odor.
<b>Odor threshold:</b>	22 ppm
<b>pH:</b>	Does not apply
<b>Freezing point:</b>	-130°F / -90°C
<b>Boiling point:</b>	180°F / 82°C
<b>Flash point:</b>	55°F / 13°C (TCC)
<b>Evaporation rate:</b>	1.7 (n-butyl acetate = 1)
<b>Flammability (solid, gas):</b>	Not applicable to liquids
<b>Upper/lower flammability or explosive limits:</b>	<b>LEL:</b> 2% <b>UEL:</b> 12.7%
<b>Vapor pressure:</b>	4.4 kPa @20°C
<b>Vapor density (Air = 1):</b>	2.07 (Air = 1)
<b>Specific gravity (H<sub>2</sub>O = 1):</b>	0.79
<b>Solubility in water:</b>	Complete
<b>Coefficient of Water/Oil Distribution:</b>	0.1 This product is equally soluble in oil and water.
<b>Auto-ignition temperature:</b>	Not available
<b>Decomposition temperature:</b>	Not available
<b>Viscosity:</b>	Not available

**9.2 Other Information**

<b>Volatiles (Weight %):</b>	100%
<b>VOC Content:</b>	790 g/l

**10. Stability and Reactivity**

**10.1 Reactivity:**

See remaining headings in Section 10.

**10.2 Chemical stability:**

Stable

**10.3 Possibility of hazardous reactions:**

None known.

**10.4 Conditions to avoid:**

Avoid heat, flame, and sparks.

**10.5 Incompatible materials :**

Strong oxidizing agents.

**10.6 Hazardous decomposition products:**

Carbon dioxide, carbon monoxide.

## 11. Toxicological Information

### 11.1 Information on toxicological effects:

#### Acute toxicity

##### Eye contact:

Direct eye contact may cause eye irritation. This irritation is minimal and expected to be transient.

##### Skin contact:

Prolonged or repeated skin exposure can remove oils, causing redness, drying and cracking. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material.

##### Irritation and Sensitization Potential:

Product may be irritating to skin and eyes. It is not a sensitizer.

##### Inhalation (Breathing):

Concentrated solvent vapors may cause irritation of the nose and throat. Prolonged exposure to excessively high vapor concentrations can result in central nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

##### Ingestion:

Ingestion of large quantities may cause irritation of the digestive tract, nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

##### Toxicity to Animals:

Isopropyl Alcohol	LD <sub>50</sub> (oral rat) 5000 mg/kg
	LD <sub>50</sub> (dermal rabbit) 12800 mg/kg
	LC <sub>50</sub> (inhl rat) 12000, 8 hours

#### Chronic Exposure:

<b>Reproductive Toxicity:</b>	Not classified as a reproductive system toxin.
<b>Mutagenicity:</b>	Not classified as a mutagen.
<b>Teratogenicity:</b>	Not classified as teratogenic or embryotoxic.
<b>Specific Target Organ Toxicity (STOT)</b>	No end point data.
<b>Toxicologically Synergistic Products:</b>	Not available.
<b>Carcinogenic Status:</b>	This substance has not been identified as a carcinogen or probable carcinogen by NTP, IARC, or OSHA, nor have any of its components.

## 12. Ecological Information

### 12.1 Toxicity:

**Ecotoxicity:** No information available.

#### Aquatic Toxicity:

**Fish (acute)** 96 h LC<sub>50</sub> Fathead Minnow > 1000 µl/l  
48 h LC<sub>50</sub> Golden Orfe 8970 - 9280 mg/l

**Aquatic crustacea (acute)** 96 h LC<sub>50</sub> Daphnid > 1000 µl/l

**12.2 Persistence and degradability:** No information available

**12.3 Bioaccumulation potential:** No information available

**12.4 Mobility in soil:** No information available

**12.5 Results of PBT and vPvB Assessment:** This product is not, nor does it contain a substance that is a PBT or vPvB.

**12.6 Other adverse effects:** None known.

## 13. Disposal Considerations

Dispose of product in accordance with National and Local Regulations.

**14. Transport Information****US DOT Domestic Ground**

<b>Transportation:</b>	Isopropyl Alcohol LTD QTY, (packages FO-2LP, FO-8LF, FO-16, FO-16C, FO-32) Isopropyl Alcohol, (packages FO-128, FO-128C)
<b>UN Number:</b>	1219
<b>UN Proper shipping name:</b>	Isopropyl Alcohol LTD QTY, (packages FO-2LP, FO-8LF, FO-16, FO-16C, FO-32) Isopropyl Alcohol, (packages FO-128, FO-128C)
<b>Transport hazard class(es):</b>	Class 3
<b>Packing group:</b>	II
<b>Environmental hazards:</b>	None known
<b>Special precautions:</b>	None known
<b>ICAO/IATA-DGR:</b>	Isopropyl Alcohol LTD QTY, (packages FO-2LP, FO-8LF, FO-16, FO-16C, FO-32) Isopropyl Alcohol, (packages FO-128, FO-128C)
<b>IMDG:</b>	Isopropyl Alcohol LTD QTY, (packages FO-2LP, FO-8LF, FO-16, FO-16C, FO-32) Isopropyl Alcohol, (packages FO-128, FO-128C)

**15. Regulatory Information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****15.1.1. NZ-Regulations**

All chemical substances in this product are listed in the New Zealand Inventory of Chemicals (NZIoC) or are exempt

This substance is to be managed using the conditions specified in an applicable Group Standard

**HSR Number**

HSR002528 Flammable Cleaning Products Group Standard

**15.1.2. EU-regulations**

- Contains no REACH substances with Annex XVII restrictions
- Contains no substance on the REACH candidate list
- Contains no REACH Annex XIV substances
- Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.
- Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

**15.1.3. Australian-regulations**

All components are listed on the AICS.

Product is classified as hazardous according to criteria of NOHSC Australia.

**15.1.4. International-regulations**

All chemical substances in this product are listed as "Active" in the US EPA (Environmental Protection Agency) "TSCA Inventory Notification (Active-Inactive) Requirements Rule" ("the Final Rule"). as of Feb. 2019 or are otherwise exempt.

**15.2 Chemical Safety Assessment**

No chemical safety assessment has been carried out for the mixture by the supplier.

**16. Other Information****Abbreviations and acronyms:**

**Product Name:** Type FO™ Fiber Optic Cleaner/Degreaser

**Revision Date:** March 14, 2022

OSHA = Occupational Safety and Health Administration  
CLP = Classification, Labeling and Packaging Regulation  
STOT = Specific Target Organ Toxicity  
LD<sub>50</sub> = Median Lethal Dose  
DNEL = Derived No Effect Level  
ACGIH = American Conference of Governmental Industrial Hygienists  
TSCA = Toxic Substances Control Act (USA)  
DSL = Domestic Substances List (Canada)  
AICS = Australian Inventory of Chemical Substances

**Mixture classification according to Regulation (EC) No 1272/2008:**

H225 Highly flammable liquid and vapor  
H319 Causes serious eye irritation  
H336 May cause drowsiness or dizziness

**Classification Procedure**

Calculation method.  
Calculation method.  
Calculation method.

**Revision Date:** March 14, 2022  
**Revision Number:** 8 NZ  
**Supersedes:** July 30, 2020  
**Other:** Not Applicable  
**Indication of Changes:** No changes.

Written in accordance with the provisions of OSHA 1910.1200 App D (2012) and Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 including New Zealand specific information. (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.