

# SAFETY DATA SHEET

## 1. Identification of the substance/mixture and of the company

### 1.1 Product identifier

**Product Name: Fiberglass Wax  
Cleaner/Water Repellent  
Saturated Wipe or Towel Package**

**Product ID numbers:** W-1, W-1C, W-1M

### 1.2 Relevant identified uses of the mixture and uses advised against

**Identified uses:** Clean and wax preparation

**List of advices against:** Not applicable.

### 1.3 Details of the supplier of the safety data sheet

**Supplier/Manufacturer:**

**American Polywater Corporation**  
11222 - 60th Street North  
Stillwater, MN 55082 USA  
Tel: 1-651-430-2270  
Email: sds@polywater.com

**Powerhouse Electric Limited**  
289 Rosebank Road,  
Avondale, Auckland 1026, NZ  
09 373 4487

### 1.4 Emergency telephone numbers

INFOTRAC: 1-800-535-5053 (USA) 1-352-323-3500 (INT'L)

NPC (National Poison Centre) 0800 764 766 and 0800 Poison

## 2. Hazards Identification

### 2.1 Classification of the substance or mixture

Classification according to USA OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).

Flam Liq 3	H226
Skin Irr 2	H315
Eye Irr 2B	H320

### 2.2 Label elements

**Contains:** Distillates (petroleum), hydrotreated light; Odorless mineral spirits; Naphtha; Mineral spirits



**Pictograms:**

**Signal word:** Danger

**Hazard Statements:**

H226	Flammable liquid and vapor.
H315	Causes skin irritation.
H320	Causes eye irritation.

**Precautionary Statements:**

P210	Keep away from sparks, flames and hot surfaces. No smoking.
P233	Keep container tightly closed.

- P242 Use only non-sparking tools.
- P280 Wear eye protection.
- P302 + P352 IF ON SKIN: Wash with plenty of water.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.
- P332 + P313 If skin irritation occurs: Get medical attention.
- P337 + P313 If eye irritation persists: Get medical attention.
- P362 + P364 Take off contaminated clothing and wash before reuse.

**2.3 Other hazards:** No information available.

**3. Composition/Information on Ingredients**

<u>Component</u>	<u>CAS #</u>	<u>EC #</u>	<u>Wt. %</u>
Mineral spirits	64475-85-0	613-601-3	3 – 8%
Distillates (petroleum) hydro treated light	64742-47-8	265-149-8	8 – 13%
Odorless Mineral Spirits	64742-48-9	265-150-3	5 - 10%
Naphtha	8032-32-4	232-453-7	3 - 8%

**4. First Aid Measures**

**4.1 Description of first aid measures**

- Eye Contact:** If eye irritation from exposure to vapors develops, move to fresh air. Flush eyes with clean water. If irritation persists, seek medical attention. For direct eye contact, flush with large quantity of water for 15 minutes. Seek medical attention.
- Skin Contact:** Remove contaminated clothing; flush skin thoroughly with water. If irritation occurs, seek medical attention.
- Inhalation (Breathing):** If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention. If breathing is difficult, provide oxygen. If not breathing, give artificial respiration. Seek immediate medical attention.
- Ingestion (Swallowing):** Do not induce vomiting or give anything by mouth unless directed to do so by medical personnel. Get medical attention if symptoms appear.

**4.2 Most important symptoms and effects, both acute and delayed**

Refer to Section 11 for more information.

**4.3 Indication of immediate medical attention and special treatment needed.**

No data available.

**5. Firefighting Measures**

**5.1 Extinguishing media:**

Carbon dioxide, water fog, dry chemical or foam.

**5.2 Special hazards arising from the substance or mixture**

**Hazardous decomposition and by-products:**

Burning generates carbon monoxide, carbon dioxide.

**5.3 Advice for firefighters**

Wear appropriate, protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Use water spray to cool fire exposed containers.

**6. Accidental Release Measures**

**6.1 Personal precautions, protective equipment and emergency procedures:**

Keep away from heat/sparks/open flames/hot surfaces. No smoking. For a spill in a confined space, provide mechanical ventilation to disperse or exhaust vapors. For emergency responders: use respiratory protection: half-face or full-face respirator with filter(s) for organic vapor for spills in a confined space.

Chemical goggles are recommended if splashes or contact with eyes is possible. For small spills: normal antistatic work clothes are usually adequate.

**6.2 Environmental precautions:**

Avoid release to the environment. Dyke the spill to prevent entry into waterways, sewers, basements or confined areas.

**6.3 Methods materials for containment and cleaning up:**

Absorb spill with sand or absorbents. Collect as much of the spilled material as possible using non-sparking tools and transfer to a container. Seal the container. Remember, adding an absorbent material does not change the toxicity or flammability hazard.

**6.4 Reference to other sections:**

Refer to Sections 4, 5, 8, and 13 for more information.

**7. Handling and Storage**

**7.1 Precautions for safe handling**

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Avoid breathing vapors or spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use only outdoors or in a well-ventilated area. For industrial or professional use only.

**7.2 Conditions for safe storage, including incompatibilities**

Store in a well-ventilated place. Keep container tightly closed. Keep cool.

**7.3 Specific end uses**

See product flyer for further information.

**8. Exposure Controls / Personal Protection**

**8.1 Control parameters**

**Exposure limits and recommendations:**

**Petroleum distillates, hydrotreated light (64742-47-8); Solvent naphtha, medium aliphatic (64742-88-7)**

Country/Source	Long-term exposure limit – 8 hr. TWA	Short-term exposure limit – 15 min
USA, OSHA PEL	2000 mg/m <sup>3</sup> , 500 ppm (as petroleum distillates (naphtha))	--
Manufacturer, RCP* TWA Alberta, Quebec, Yukon, British Columbia, Saskatchewan, Ontario*	1200 mg/m <sup>3</sup>	--
	Not established	Not established

**Mineral spirits (64475-85-0)**

Country/Source	Long-term exposure limit – 8 hr. TWA	Short-term exposure limit – 15 min
USA, OSHA PEL	Not established	--
Ontario Alberta, Quebec, Yukon, British Columbia, Saskatchewan*	525 mg/m <sup>3</sup>	--
	Not established	Not established

*\* Manitoba, Newfoundland and Labrador, Nova Scotia, and Prince Edward Island are all based on the current ACGIH TLVs. New Brunswick is based on an older version ACGIH. Nunavet and Northwest Territories are based heavily on current ACGIH TLVs.*

**8.2 Exposure controls**

**Respiratory protection:**

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Use a respirator or gas mask with cartridges for organic vapors (NIOSH-approved) or use supplied air equipment.

**Protective gloves:**

For repeated or prolonged skin contact, the use of impermeable gloves is recommended to prevent drying and possible irritation.

Suggested Material: Nitrile Rubber  
Suggested Thickness: For short term contact (<15 minutes), splashes use 0.2 mm. For full contact use 0.4 mm

Exact break-through time has not been determined. Guidance is based on similar chemistry/material. Maximum wearing time should be determined based on 50 % of the penetration time determined by EN 374 part III.

**Eye protection:**

Safety glasses recommended.

**Other protective equipment:**

It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.

**9. Physical and Chemical**

**9.1 Information of basic physical and chemical properties**

<b>Appearance:</b>	Yellow liquid.
<b>Odor threshold:</b>	Banana odor
<b>pH:</b>	Not available
<b>Freezing point:</b>	Not available
<b>Boiling point:</b>	Not available
<b>Flash point:</b>	Not available
<b>Evaporation rate:</b>	Not available
<b>Flammability (solid, gas):</b>	Not applicable to liquids
<b>Flammability limits:</b>	Not available
<b>Vapor pressure:</b>	Not available
<b>Vapor density (Air = 1):</b>	Not available
<b>Specific gravity (H<sub>2</sub>O = 1):</b>	0.98
<b>Solubility in water:</b>	Insoluble
<b>Coefficient of Water/Oil Distribution:</b>	Not available
<b>Auto-ignition temperature:</b>	Not available
<b>Decomposition temperature:</b>	Not available
<b>Viscosity:</b>	Not available

**9.2 Other Information**

<b>VOC Content:</b>	Not available
---------------------	---------------

**10. Stability and Reactivity**

**10.1 Reactivity:**

See remaining headings in Section 10.

**10.2 Chemical stability:**

Stable

**10.3 Possibility of hazardous reactions:**

None known.

**10.4 Conditions to avoid:**

Avoid heat, flame, and sparks.

**10.5 Incompatible materials :**

Strong acids, alkalis, oxidizing agents.

**10.6 Hazardous decomposition products:**

Aldehydes, carbon dioxide, carbon monoxide.

**11. Toxicological Information**

**11.1 Information on toxicological effects:**

**Acute toxicity**

**Eye contact:**

Direct eye contact causes serious eye irritation.

**Skin contact:**

Prolonged or repeated skin exposure can remove oils, causing redness, drying and cracking. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material.

**Irritation and Sensitization Potential:**

Product may be irritating to skin and eyes. It is not a sensitizer.

**Inhalation (Breathing):**

Concentrated solvent vapors may cause irritation of the nose and throat. Prolonged exposure to excessively high vapor concentrations can result in central nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

**Ingestion:**

Ingestion of large quantities may cause irritation of the digestive tract, nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

**Toxicity to Animals:**

Calculated values: LD<sub>50</sub> (oral rat) >2,000 mg/kg  
 LD<sub>50</sub> (dermal rabbit) >2,000 mg/kg  
 LC<sub>50</sub> (inhl rat) >5 mg/L

**Chronic Exposure:**

**Reproductive Toxicity:** No data available.  
**Mutagenicity:** No data available  
**Teratogenicity:** No data available  
**Specific Target Organ Toxicity (STOT):** Kidneys, lungs, liver, mucous membranes, upper respiratory tract, skin, central nervous system (CNS).  
**Toxicologically Synergistic Products:** Not available.  
**Carcinogenic Status:** This substance has not been identified as a carcinogen or probable carcinogen by NTP, IARC, or OSHA, nor have any of its components. Silica dust is not in a respirable form.

**12. Ecological Information**

**12.1 Toxicity:**

**Ecotoxicity:** No information available.

**Aquatic Toxicity:** No information available.

**12.2 Persistence and degradability:** No information available

**12.3 Bioaccumulation potential:** No information available

**12.4 Mobility in soil:** No information available

**12.5 Results of PBT and vPvB Assessment:** This product is not, nor does it contain a substance that is a PBT or vPvB.

**12.6 Other adverse effects:** None known.

**13. Disposal Considerations**

Dispose of product in accordance with National and Local Regulations.

#### 14. Transport Information

<b>US DOT Domestic Ground Transportation:</b>	Fiberglass Wax Cleaner/Water Repellent Type W-1 is classified as a Combustible Liquid and is not regulated for Domestic ground transportation. No special packaging, marking, labeling, and paperwork requirements apply.
<b>UN Number:</b>	UN 3175
<b>UN Proper Shipping Name:</b>	Solids Containing Flammable Liquid, N.O.S., (Contains: Petroleum distillates)
<b>Class:</b>	Class 4.1
<b>Packing Group:</b>	II
<b>ICAO/IATA-DGR:</b>	UN 3175, Solids Containing Flammable Liquid, N.O.S., (Contains, Petroleum distillates)
<b>IMDG:</b>	UN 3175, Solids Containing Flammable Liquid, N.O.S., (Contains, Petroleum distillates)

#### 15. Regulatory Information

##### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

###### 15.1.1. NZ-Regulations

All chemical substances in this product are listed in the New Zealand Inventory of Chemicals (NZIoC) or are exempt

This substance is to be managed using the conditions specified in an applicable Group Standard

###### HSR Number

HSR002525 Cleaning Products (Combustible) Group Standard 2017

###### 15.1.2. EU-regulations

- Contains no REACH substances with Annex XVII restrictions
- Contains no substance on the REACH candidate list
- Contains no REACH Annex XIV substances
- Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.
- Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

###### 15.1.3. Australian-regulations

Classified as a Schedule 5 (S5) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Safework Australia criteria is based on the Globally Harmonized System (GHS) of Classification and Labelling of Chemicals.

All components are listed on the AICS.

Product is classified as hazardous according to criteria of NOHSC Australia.

###### 15.1.4. International-regulations

All chemical substances in this product are listed as "Active" in the US EPA (Environmental Protection Agency) "TSCA Inventory Notification (Active-Inactive) Requirements Rule" ("the Final Rule"). as of Feb. 2019 or are otherwise exempt.

##### 15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier

#### 16. Other Information

##### Abbreviations and acronyms:

OSHA = Occupational Safety and Health Administration

**Product Name:** Fiberglass Wax Cleaner/Water Repellent Wipe (W-1)

**Revision Date:** March 14, 2022

CLP = Classification, Labeling and Packaging Regulation  
STOT = Specific Target Organ Toxicity  
LD<sub>50</sub> = Median Lethal Dose  
DNEL = Derived No Effect Level  
ACGIH = American Conference of Governmental Industrial Hygienists  
TSCA = Toxic Substances Control Act (USA)  
DSL = Domestic Substances List (Canada)  
AICS = Australian Inventory of Chemical Substances

**Mixture classification according to Regulation (EC) No 1272/2008:**

H226 Flammable liquid and vapor.  
H315 Causes skin irritation.  
H320 Causes eye irritation.

**Classification Procedure**

Physical Testing  
Calculation method.  
Calculation method.

**Revision Date:** March 14, 2022  
**Revision Number:** 9 NZ  
**Supersedes:** December 3, 2021  
**Other:** Not Applicable  
**Indication of Changes:** No changes.

Written in accordance with the provisions of OSHA 1910.1200 App D (2012) and Canada HPR (SOR/2015-17) (WHMIS 2015). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.