

Polywater®

InstaGrout™



UTILITY ENCLOSURE PAD SEALANT





A Thorough and Easy Solution to Prevent Costly Unplanned Outages

Polywater® InstaGrout™ is a pourable, two-part urethane foam that seals pad-mounted equipment openings to prevent outages and service disruptions caused by animal or moisture ingress. It is safer to use and more effective than concrete grout and will not collapse during changeouts. Polywater InstaGrout thoroughly adheres to various pad and conduit materials, creating a permanent seal that can be re-entered to install new ducts.




FEATURES AND BENEFITS

- **SECURES ENCLOSURES**
Keeps rodents, snakes, insects, and water from entering enclosures
- **EASY TO USE**
Ready to mix and apply—no water or electricity needed
- **CUSTOM INSTALLATION**
Self-levels and expands to seal the entire opening
- **RE-ENTERABLE**
Saw or drill to install new conduit stub ups, cables, or ground rods
- **PROTECTS**
Permanent protection through weather extremes or equipment changeouts

	CATALOG #	PACKAGE DESCRIPTION	UNITS/CASE
	PMT-1	Kit Includes: 1 – 750 ml Burst Pack; 1 – Pair of Gloves; 1 – Instruction Sheet <i>Kit covers 1 square foot (approx.) at a three-inch depth/930 cm² at 7.6 cm depth</i>	2
	PMT-2	Kit Includes: 1 – 1500 ml Burst Pack; 1 – Pair of Gloves; 1 – Instruction Sheet <i>Kit covers 2 square feet (approx.) at a three-inch depth/1860 cm² @ 7.6 cm depth</i>	2
	PMT-3	Kit Includes: 1 – Bottle Part A; 1 – Bottle Part B; 1 – Mixing Pail; 1 – Mixing Stick; 1 – Pair of Gloves; 1 – Instruction Sheet <i>Kit covers 3 square feet (approx.) at a three-inch depth/2790 cm² at 7.6 cm depth</i>	1
	PMT-10	Kit Includes: 1 – Jug Part A; 1 – Jug Part B; 1 – Mixing Pail; 1 – Pair of Gloves; 1 – Instruction Sheet <i>Kit covers 10 square feet (approx.) at a three-inch depth/9290 cm² at 7.6 cm depth</i>	1

Contents of the Polywater InstaGrout PMT-3 Kit.

SPECIFICATIONS AND APPLICATIONS



- Material Compatibility:** Cured Polywater InstaGrout Sealant is compatible with cable jacket materials, conduits, and various transformer pad materials. The foam is an inert solid that will not compromise the jacket material.
- Adhesion:** Polywater InstaGrout Sealant has good adhesion to a variety of materials found in electrical cabinets, including PVC, copper, aluminum, fiberglass pads, polymer concrete pads, polyester, and polyethylene.
- Water and Chemical Resistance:** Polywater InstaGrout Sealant does not absorb water and is chemically resistant to gasoline, oils, dilute acids, and bases.

polywater.com | +1 651-430-2270

IMPORTANT NOTICE: The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct, indirect, or consequential damages resulting from a product's use, regardless of the legal theory asserted.

© 2022 American Polywater Corporation LIT-INSTAGROUTFLYER/REV000

Polywater®
Solutions at work.

American Polywater Corporation
11222 60th Street N.
Stillwater, MN 55082 USA

+1 651-430-2270 Main
+31 10 233 0578 Europe, Middle East, N. Africa
email: support@polywater.com