

Section 1. Identification

Product identifier

Product Identity Type P7™ Penetrating Oil Aerosol
Other means of identification P7-XXX (where XXX is the package code)

Relevant identified uses of the substance or mixture and uses advised against

Clear, light to amber liquid with mild hydrocarbon odor

Details of the supplier of the safety data sheet

Company Name American Polywater Corporation
11222 - 60th Street North
Stillwater, MN 55082 USA

Emergency
24 hour Emergency Telephone No. INFOTRAC: 1-800-535-5053 (USA)
1-352-323-3500 (INT'L)

Customer Service: Tel: 1-651-430-2270
Email: sds@polywater.com

Section 2. Hazard(s) identification

Classification of the substance or mixture under US OSHA's Hazard Communication Standard (1910.1200) revised 2024 and Canadian Hazardous Products Regulations (SOR/2015-17) (GHS revision 7)

Flammable Aerosol, category 2;H223
H229
Specific target organ toxicity, repeated exposure category 1;H372

Simple Asphyxiant

Flammable aerosol.
Pressurized container: May burst if heated.
Causes damage to organs through prolonged or repeated exposure. Specific Target Organs: (central nervous system)
May displace oxygen and cause rapid suffocation.

Label elements



Danger

H223 Flammable aerosol.

H229 Pressurized container: May burst if heated.

H372 Causes damage to organs through prolonged or repeated exposure.
May displace oxygen and cause rapid suffocation.

[Prevention]

P210 Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P260 Do not breathe dust, fume, mist, vapors or spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

[Response]

P301+312 IF SWALLOWED: Call a POISON CENTER, doctor or physician if you feel unwell.

P304+312 IF INHALED: Call a poison center or doctor or physician if you feel unwell.

P314 Get Medical advice or attention if you feel unwell.

P332+313 If skin irritation occurs: Get medical attention.

[Storage]

P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F.

[Disposal]

P501 Dispose of contents or container in accordance with local and national regulations.

Other hazards

May displace oxygen and cause rapid suffocation.

This product contains no PBT/vPvB/vPvM chemicals.

This product contains no endocrine disrupting chemicals.

Does not contain component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS) per the Organisation for Economic Co-operation and Development (OECD) list of Per- and Polyfluoroalkyl Substances (PFASs).

Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of US OSHA's Hazard Communication Standard (1910.1200) revised 2024 and Canadian Hazardous Products Regulations (SOR/2015-17) (GHS revision 7)

| Ingredient/Chemical Designations | Weight % | GHS Classification | Notes |
|---|----------|---|-------|
| Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil-unspecified CAS Number: 64742-52-5 Synonyms: Polymer Binders and Adhesive, Distillate (petroleum) hydrotreated heavy naphthenic | 30 - 60 | Not Classified | ----- |
| Solvent naphtha (petroleum), medium aliphatic CAS Number: 64742-88-7 Synonyms: No available information | 30 - 60 | Specific target organ toxicity, repeated exposure category 1;H372 Aspiration hazard, category 1;H304 | ----- |
| Barium petroleum sulfonate CAS Number: 61790-48-5 Synonyms: Sulfonic acids, petroleum, barium salts | 10 - 30 | Acute toxicity(oral), category 4;H302 Acute toxicity(inhalation), category 4;H332 | ----- |
| Propane CAS Number: 74-98-6 Synonyms: No available information | 7 - 13 | Flammable Gas, category 1;H220 Liquified Gas;H280 Simple Asphyxiant | ----- |
| Isobutane CAS Number: 75-28-5 Synonyms: Propane, 2-methyl- | 7 - 13 | Flammable Gas, category 1;H220 Gas under pressure;H280 | ----- |
| 2-Butoxy-ethanol CAS Number: 111-76-2 Synonyms: 2-butoxyethanol, BUTOXYETHANOL, butyl cellosolve, Ethylene glycol monobutyl ether, Glycol Ether, Solvent A-1 | 7 - 13 | Acute toxicity(inhalation), category 3;H331 Acute toxicity(oral), category 4;H302 Serious eye damage / eye irritation, category 2;H319 Skin corrosion/irritation category 2;H315 | ----- |

The actual concentration or concentration range is withheld as a trade secret.

*PBT/vPvB - PBT, vPvM or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

Description of first aid measures

- General** In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
- Eyes** Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
- Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
- Ingestion** If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Overview No chronic toxicity or long term toxicity information available. Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Skin Causes mild skin irritation.

Section 5. Fire-fighting measures

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.
Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust, fume, mist, vapors or spray.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

ERG Guide No.

126

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage

Precautions for safe handling

Handle containers carefully to prevent damage and spillage.
See section 2 for further details. - [Prevention]

Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong oxidizing agents and acids.
See section 2 for further details. - [Storage]

Specific end use(s)

No available information

Section 8. Exposure controls / personal protection

Control parameters

Exposure Limits

| CAS No. | Ingredient | Source | Value |
|---------|------------|---------------------------|--|
| 74-98-6 | Propane | ACGIH | (D) Simple Asphyxiant - (EX) Explosion hazard |
| | | OSHA | 1000 ppm, 1800 mg/m ³ |
| | | NIOSH | TWA 1000 ppm (1800 mg/m ³) |
| | | Alberta | 1000 ppm TWA |
| | | British Columbia | No Established Limit |
| | | Manitoba | See Appendix F: Minimal Oxygen Content, explosion hazard |
| | | New Brunswick | No Established Limit |
| | | Newfoundland and Labrador | See Appendix F: Minimal Oxygen Content, explosion hazard |
| | | Nova Scotia | See Appendix F: Minimal Oxygen Content, explosion hazard |
| | | Northwest Territories | 1000 ppm TWA 1250 ppm STEL |
| | | Nunavut | 1000 ppm TWA 1250 ppm STEL |
| | | Ontario | see Appendix F: Minimal Oxygen Content |
| | | Prince Edward Island | See Appendix F: Minimal Oxygen Content, explosion hazard |
| | | Quebec | 1000 ppm TWAEV; 1800 mg/m ³ TWAEV |
| 75-28-5 | Isobutane | Saskatchewan | 1000 ppm TWA 1250 ppm STEL |
| | | Yukon | No Established Limit |
| | | ACGIH | 1000 ppm (EX) Explosion hazard |
| | | OSHA | No Established Limit |
| | | NIOSH | TWA 800 ppm (1900 mg/m ³) |
| | | Alberta | No Established Limit |
| | | British Columbia | No Established Limit |
| | | Manitoba | 1000 ppm STEL (explosion hazard, listed under Butane, isomers) |
| | | New Brunswick | No Established Limit |
| | | Newfoundland and Labrador | 1000 ppm STEL (explosion hazard, listed under Butane, isomers) |

| CAS No. | Ingredient | Source | Value |
|------------|--|---------------------------|--|
| | | Nova Scotia | 1000 ppm STEL (explosion hazard, listed under Butane, isomers) |
| | | Northwest Territories | 1000 ppm TWA (listed under Butane, all isomers) 1250 ppm STEL (listed under Butane, all isomers) |
| | | Nunavut | 1000 ppm TWA (listed under Butane, all isomers) 1250 ppm STEL (listed under Butane, all isomers) |
| | | Ontario | 1000 ppm STEL (listed under Butane, all isomers) |
| | | Prince Edward Island | 1000 ppm STEL (explosion hazard, listed under Butane, isomers) |
| | | Quebec | No Established Limit |
| | | Saskatchewan | 1000 ppm TWA (listed under Butane, all isomers) 1250 ppm STEL (listed under Butane, all isomers) |
| | | Yukon | No Established Limit |
| 111-76-2 | 2-Butoxy-ethanol | ACGIH | 20 ppm |
| | | OSHA | 50 ppm, 240 mg/m ³ |
| | | NIOSH | TWA 5 ppm (24 mg/m ³) [skin] |
| | | Alberta | 20 ppm TWA; 97 mg/m ³ TWA |
| | | British Columbia | 20 ppm TWA |
| | | Manitoba | 20 ppm TWA |
| | | New Brunswick | 25 ppm TWA; 121 mg/m ³ TWA |
| | | Newfoundland and Labrador | 20 ppm TWA |
| | | Nova Scotia | 20 ppm TWA |
| | | Northwest Territories | 20 ppm TWA 30 ppm STEL |
| | | Nunavut | 20 ppm TWA 30 ppm STEL |
| | | Ontario | 20 ppm TWA |
| | | Prince Edward Island | 20 ppm TWA |
| | | Quebec | 20 ppm TWAEV; 97 mg/m ³ TWAEV |
| | | Saskatchewan | 20 ppm TWA 30 ppm STEL |
| Yukon | 50 ppm TWA; 240 mg/m ³ TWA 150 ppm STEL; 720 mg/m ³ STEL | | |
| 61790-48-5 | Barium petroleum sulfonate | ACGIH | 0.5 mg/m ³ (as Ba) |
| | | OSHA | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Alberta | No Established Limit |
| | | British Columbia | No Established Limit |
| | | Manitoba | No Established Limit |
| | | New Brunswick | No Established Limit |
| | | Newfoundland and Labrador | No Established Limit |
| | | Nova Scotia | No Established Limit |
| | | Northwest Territories | No Established Limit |
| | | Nunavut | No Established Limit |
| | | Ontario | No Established Limit |
| | | Prince Edward Island | No Established Limit |
| | | Quebec | No Established Limit |
| | | Saskatchewan | No Established Limit |
| Yukon | No Established Limit | | |
| 64742-52-5 | Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil-unspecified | ACGIH | No Established Limit |
| | | OSHA | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Alberta | No Established Limit |
| | | British Columbia | No Established Limit |
| | | Manitoba | No Established Limit |
| | | New Brunswick | No Established Limit |
| | | Newfoundland and Labrador | No Established Limit |
| | | Nova Scotia | No Established Limit |

| CAS No. | Ingredient | Source | Value |
|------------|---|---------------------------|----------------------|
| | | Northwest Territories | No Established Limit |
| | | Nunavut | No Established Limit |
| | | Ontario | No Established Limit |
| | | Prince Edward Island | No Established Limit |
| | | Quebec | No Established Limit |
| | | Saskatchewan | No Established Limit |
| | | Yukon | No Established Limit |
| 64742-88-7 | Solvent naphtha (petroleum), medium aliphatic | ACGIH | No Established Limit |
| | | OSHA | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Alberta | No Established Limit |
| | | British Columbia | No Established Limit |
| | | Manitoba | No Established Limit |
| | | New Brunswick | No Established Limit |
| | | Newfoundland and Labrador | No Established Limit |
| | | Nova Scotia | No Established Limit |
| | | Northwest Territories | No Established Limit |
| | | Nunavut | No Established Limit |
| | | Ontario | No Established Limit |
| | | Prince Edward Island | No Established Limit |
| | | Quebec | No Established Limit |
| | | Saskatchewan | No Established Limit |
| | | Yukon | No Established Limit |

Contains mineral oil. The exposure limits for oil mist are 5 mg/m³OSHA PEL and 5 mg/m³ACGIH.

Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes Protective safety glasses recommended

Skin Avoid skin contact. Protective gloves recommended.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

Information on basic physical and chemical properties

| | |
|--|--|
| Physical State | Liquid |
| Color | Clear, light to amber liquid with mild hydrocarbon odor |
| Odor | No available information |
| Odor threshold | No available information |
| Melting point / freezing point | No available information |
| Initial boiling point and boiling range | 106°F / 41°C |
| Flammability (solid, gas) | Not Applicable |
| Upper/lower flammability or explosive limits | Lower Explosive Limit: 0.6% Upper Explosive Limit: 6.5% |
| Flash Point | -100°F/-74°C - estimated for propellant, lowest flashing component |
| Auto-ignition temperature | Product is not self-igniting |
| Decomposition temperature | No available information |
| pH | No available information |
| Viscosity | No available information |
| Solubility in Water | No available information |
| Partition coefficient n-octanol/water (Log Kow) | No available information |
| Vapor pressure (Pa) | 6.6 hPa (5 mmHg) @20°C |
| Relative Density | No available information |
| Vapor Density | No available information |
| Evaporation rate (Ether = 1) | No available information |
| Oxidising properties | No available information |
| Explosive properties | No available information |
| % Volatile | 49.3% |

Other information

DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)

Section 10. Stability and reactivity

Reactivity

Hazardous Polymerization will not occur.

Chemical stability

Stable under normal circumstances.

Possibility of hazardous reactions

No available information

Conditions to avoid

Excessive heat and open flame.

Incompatible materials

Strong oxidizing agents and acids.

Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. 2-butoxyethanol and its acetate are readily absorbed through the skin and will cause harmful effects on the blood.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

| Ingredient | Oral LD50, mg/kg | Skin LD50, mg/kg | Inhalation Vapor LC50, mg/L/4hr | Inhalation Dust/Mist LC50, mg/L/4hr | Inhalation Gas LC50, ppm |
|--|--------------------------------|--------------------|---------------------------------|-------------------------------------|--------------------------|
| Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil-unspecified - (64742-52-5) | > 5,000.00, Rat - Category: NA | No data available. | No data available. | 5.70, Rat - Category: NA | No data available. |
| Solvent naphtha (petroleum), medium aliphatic - (64742-88-7) | | | | | |

| Ingredient | Oral LD50, mg/kg | Skin LD50, mg/kg | Inhalation Vapor LC50, mg/L/4hr | Inhalation Dust/Mist LC50, mg/L/4hr | Inhalation Gas LC50, ppm |
|---|------------------------------------|------------------------------------|----------------------------------|-------------------------------------|----------------------------------|
| | 6,000.00, Rat - Category: NA | 3,000.00, Rabbit - Category: 5 | No data available. | No data available. | No data available. |
| Barium petroleum sulfonate - (61790-48-5) | > 5,000.00, Rat - Category: NA | No data available. | > 1.90, Rat - Category: NA | No data available. | No data available. |
| Propane - (74-98-6) | No data available. | No data available. | 658.00, Rat - Category: NA | No data available. | No data available. |
| Isobutane - (75-28-5) | No data available. | No data available. | 658.00, Rat - Category: NA | No data available. | No data available. |
| 2-Butoxy-ethanol - (111-76-2) | 1,414.00, Guinea Pig - Category: 4 | 2,000.00, Guinea Pig - Category: 4 | 3.00, ATE Estimate - Category: 3 | No data available. | 633.00, Guinea Pig - Category: 3 |

Carcinogen Data

| CAS No. | Ingredient | Source | Value |
|------------|---|--------|----------------------|
| 74-98-6 | Propane | IARC | No |
| | | ACGIH | No Established Limit |
| 75-28-5 | Isobutane | IARC | No |
| | | ACGIH | No Established Limit |
| 111-76-2 | 2-Butoxy-ethanol | IARC | Group 3 |
| | | ACGIH | A3 |
| 61790-48-5 | Barium petroleum sulfonate | IARC | No |
| | | ACGIH | No Established Limit |
| 64742-52-5 | Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil-unspecified | IARC | No |
| | | ACGIH | No Established Limit |
| 64742-88-7 | Solvent naphtha (petroleum), medium aliphatic | IARC | No |
| | | ACGIH | No Established Limit |

| Classification | Category | Hazard Description |
|-------------------------------|----------|--------------------|
| Acute toxicity (oral) | --- | Not Applicable |
| Acute toxicity (dermal) | --- | Not Applicable |
| Acute toxicity (inhalation) | --- | Not Applicable |
| Skin corrosion/irritation | --- | Not Applicable |
| Serious eye damage/irritation | --- | Not Applicable |
| Respiratory sensitization | --- | Not Applicable |
| Skin sensitization | --- | Not Applicable |

| | | |
|------------------------|-----|---|
| Germ cell mutagenicity | --- | Not Applicable |
| Carcinogenicity | --- | Not Applicable |
| Reproductive toxicity | --- | Not Applicable |
| STOT-single exposure | --- | Not Applicable |
| STOT-repeated exposure | 1 | Causes damage to organs through prolonged or repeated exposure. |
| Aspiration hazard | --- | Not Applicable |

Possible routes of entry:

Inhalation, ingestion, skin contact, and skin absorption.

Symptoms and effects, both acute and delayed:

No chronic toxicity or long term toxicity information available. Treat symptomatically.

Skin Causes mild skin irritation.
Ingestion May be harmful if swallowed.

Section 12. Ecological information

Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

| Ingredient | 96 hr LC50 fish, mg/L | 48 hr EC50 crustacea, mg/L | ErC50 algae, mg/L |
|--|--------------------------------|----------------------------|-----------------------------------|
| Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil-unspecified - (64742-52-5) | 5,000.00, Oncorhynchus mykiss | 1,000.00, Daphnia magna | 1,000.00, Scenedesmus subspicatus |
| Solvent naphtha (petroleum), medium aliphatic - (64742-88-7) | 800.00, Pimephales promelas | 100.00, Daphnia magna | 450.00, Selenastrum capricornutum |
| Barium petroleum sulfonate - (61790-48-5) | > 10,000.00, Sheepshead minnow | > 1,000.00, Daphnia magna | 1,000.00, |
| Propane - (74-98-6) | 49.90, Fish | 69.43, Daphnia sp | 19.37, Algae |
| Isobutane - (75-28-5) | | | |

| Ingredient | 96 hr LC50 fish, mg/L | 48 hr EC50 crustacea, mg/L | ErC50 algae, mg/L |
|-------------------------------|-----------------------|----------------------------|--------------------|
| | No data available. | No data available. | No data available. |
| 2-Butoxy-ethanol - (111-76-2) | 1,250.00, | 690.00, | 623.00, |

Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

No available information

Mobility in soil

No available information

Results of PBT and vPvB assessment

This product contains no PBT/vPvB/vPvM chemicals.

Other adverse effects

No available information

Section 13. Disposal considerations

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.

Section 14. Transport information

Classification Method: Classified as per Part 2, Sections 2.1-2.8 of the Transportation of Dangerous Goods Regulations.

DOT (Domestic Surface Transportation)

| | |
|-----------------------------------|----------------------------|
| UN number | UN1950 |
| UN proper shipping name | Aerosols, Limited Quantity |
| Transport hazard class(es) | 2.1 |
| Sub Class | Not Applicable |
| Packing group | Not Applicable |

TDG (Domestic Surface Transportation)

| | |
|-----------------------------------|----------------------------|
| UN number | UN1950 |
| UN proper shipping name | Aerosols, Limited Quantity |
| Transport hazard class(es) | 2.1 |
| Sub Class | Not Applicable |
| Packing group | Not Applicable |

IMO / IMDG (Ocean Transportation)

| | |
|-----------------------------------|----------------------------|
| UN number | UN1950 |
| UN proper shipping name | Aerosols, Limited Quantity |
| Transport hazard class(es) | 2.1 |
| Sub Class | Not Applicable |
| Packing group | Not Applicable |

ICAO/IATA

| | |
|-----------------------------------|----------------------------|
| UN number | UN1950 |
| UN proper shipping name | Aerosols, Limited Quantity |
| Transport hazard class(es) | 2.1 |
| Sub Class | Not Applicable |
| Packing group | Not Applicable |

Environmental hazards

IMDG Marine Pollutant: No;

Special precautions for user

No available information

Section 15. Regulatory information

**Regulatory
Overview**

The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

This product has been classified in accordance with US OSHA's Hazard Communication Standard (1910.1200) revised 2024 and Canadian Hazardous Products Regulations (SOR/2015-17 amended 2022-12-15) (GHS revision 7) and the SDS contains all of the information required by those regulations.

All components of this material are either listed or exempt from listing on the TSCA Inventory.

All components of this material are either listed or exempt from listing on the DSL or NDSL Inventories.

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

2-Butoxy-ethanol

Barium petroleum sulfonate

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 Label Warning:

This product contains no chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

Revision Date

9 October, 2025

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H372 Causes damage to organs through prolonged or repeated exposure.

End of Document