

Section 1. Identification

Product identifier

Product Identity Type RP™ Electrical Contact Cleaner Aerosol
Other means of identification RP-16X (where X is the package code)

Relevant identified uses of the substance or mixture and uses advised against

See Technical Data Sheet.

Details of the supplier of the safety data sheet

Company Name American Polywater Corporation
11222 - 60th Street North
Stillwater, MN 55082 USA

Emergency
24 hour Emergency Telephone No. INFOTRAC: 1-800-535-5053 (USA)
1-352-323-3500 (INT'L)

Customer Service: Tel: 1-651-430-2270
Email: sds@polywater.com

Section 2. Hazard(s) identification

Classification of the substance or mixture under US OSHA's Hazard Communication Standard (1910.1200) revised 2024 and Canadian Hazardous Products Regulations (SOR/2015-17) (GHS revision 7)

Flammable Aerosol, category 2;H223
H229
Reproductive toxicity, category 2;H361F
Specific target organ toxicity, Single
exposure category 3;H336
Specific target organ toxicity, repeated
exposure category 1;H372

Flammable aerosol.
Pressurized container: May burst if heated.
Suspected of damaging fertility.
May cause drowsiness or dizziness.

Causes damage to organs through prolonged
or repeated exposure.

Aspiration hazard, category 1;H304
Simple Asphyxiant

May be fatal if swallowed and enters airways.
May displace oxygen and cause rapid suffocation.

Label elements



Danger

H223 Flammable aerosol.

H229 Pressurized container: May burst if heated.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness and dizziness.

H361f Suspected of damaging fertility.

H372 Causes damage to organs through prolonged or repeated exposure.

May displace oxygen and cause rapid suffocation.

[Prevention]

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

P211 Do not spray on an open flame or other ignition source.

P233 Keep container tightly closed.

P251 Pressurized container: Do not pierce or burn, even after use.

P260 Do not breathe dust, fume, mist, vapors or spray.

P262 Do not get in eyes, on skin, or on clothing.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves, eye protection, and face protection.

[Response]

P301+310 IF SWALLOWED: Immediately call a POISON CENTER, doctor or physician.

P304+340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+313 IF exposed or concerned: Get medical advice or attention.

P312 Call a POISON CENTER, doctor or physician if you feel unwell.

P314 Get Medical advice or attention if you feel unwell.

P331 Do NOT induce vomiting.

P332+313 If skin irritation occurs: Get medical attention.

P391 Collect spillage.

[Storage]

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F.

[Disposal]

P501 Dispose of contents or container in accordance with local and national regulations.

Other hazards

May displace oxygen and cause rapid suffocation.

This product contains no PBT/vPvB/vPvM chemicals.

This product contains no endocrine disrupting chemicals.

Does not contain component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS) per the Organisation for Economic Co-operation and Development (OECD) list of Per- and Polyfluoroalkyl Substances (PFASs).

Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of US OSHA's Hazard Communication Standard (1910.1200) revised 2024 and Canadian Hazardous Products Regulations (SOR/2015-17) (GHS revision 7)

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
2-methylpentane CAS Number: 107-83-5 Synonyms: Pentane, 2-methyl-	45 - 70	Flammable Liquid, category 2;H225 Aspiration hazard, category 1;H304 Skin corrosion/irritation category 2;H315 Specific target organ toxicity, Single exposure category 3;H336 Aquatic toxicity (chronic), category 2;H411	-----
Naphtha (petroleum), hydrotreated light CAS Number: 64742-49-0 Synonyms: Aliphatic Hydrocarbon	10 - 30	Aspiration hazard, category 1;H304 Flammable Liquid, category 1;H224	-----
Distillates (petroleum), light distillate hydrotreating process, low-boiling CAS Number: 68410-97-9 Synonyms: Light distillate hydrotreater stabilizer overhead liquid	10 - 30	Aspiration hazard, category 1;H304	-----

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Pentane CAS Number: 109-66-0 Synonyms: C5 n-alkane, n-pentane	7 - 13	Flammable Liquid, category 2;H225 Aspiration hazard, category 1;H304 Specific target organ toxicity, Single exposure category 3;H336 Aquatic toxicity (chronic), category 2;H411	----
Carbon dioxide CAS Number: 124-38-9 Synonyms: No available information	3 - 7	Gas under pressure;H280 Simple Asphyxiant	----
2-Methoxy-1-Methylethyl Acetate CAS Number: 108-65-6 Synonyms: Propylene glycol monomethyl ether acetate, 1-Methoxy-2-propyl acetate	3 - 7	Flammable Liquid, category 3;H226	----
Hexane CAS Number: 110-54-3 Synonyms: N-HEXANE	0.5 - 1.5	Flammable Liquid, category 2;H225 Reproductive toxicity, category 2;H361f Aspiration hazard, category 1;H304 Skin corrosion/irritation category 2;H315 Specific target organ toxicity, Single exposure category 3;H336 Aquatic toxicity (chronic), category 2;H411 Specific target organ toxicity, repeated exposure category 1;H372	----

The actual concentration or concentration range is withheld as a trade secret.

*PBT/vPvB - PBT, vPvM or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

Ingestion If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Overview Reproductive or genetic defect hazard. Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Inhalation May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Skin Causes mild skin irritation.

Section 5. Fire-fighting measures

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.
Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.
Keep away from heat, sparks, open flames, and other ignition sources - No smoking.
Do not spray on an open flame or other ignition source.
Keep container tightly closed.
Pressurized container: Do not pierce or burn, even after use.
Do not breathe dust, fume, mist, vapors or spray.
Do not get in eyes, on skin, or on clothing.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

ERG Guide No.

128

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).
Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8.
Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage

Precautions for safe handling

Handle containers carefully to prevent damage and spillage.
See section 2 for further details. - [Prevention]

Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong oxidizing agents and acids.
See section 2 for further details. - [Storage]

Specific end use(s)

No available information

Section 8. Exposure controls / personal protection

Control parameters

Exposure Limits

CAS No.	Ingredient	Source	Value
107-83-5	2-methylpentane	ACGIH	200 ppm
		OSHA	No Established Limit
		NIOSH	No Established Limit
		Alberta	500 ppm TWA (listed under Hexane (all isomers except n-Hexane)); 1760 mg/m ³ TWA (listed under H 1000 ppm STEL (listed under Hexane (all isomers except n-Hexane)); 3500 mg/m ³ STEL (listed unde
		British Columbia	No Established Limit
		Manitoba	500 ppm TWA (listed under Hexane isomers other than n-hexane) 1000 ppm STEL (listed under Hexane isomers other than n-hexane)
		New Brunswick	No Established Limit
		Newfoundland and Labrador	500 ppm TWA (listed under Hexane isomers other than n-hexane) 1000 ppm STEL (listed under Hexane isomers other than n-hexane)
		Nova Scotia	500 ppm TWA (listed under Hexane isomers other than n-hexane) 1000 ppm STEL (listed under Hexane isomers other than n-hexane)
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	500 ppm TWA (listed under Hexane, isomers, other than n-Hexane) 1000 ppm STEL (listed under Hexane, isomers, other than n-Hexane)
		Prince Edward Island	500 ppm TWA (listed under Hexane isomers other than n-hexane) 1000 ppm STEL (listed under Hexane isomers other than n-hexane)
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
108-65-6	2-Methoxy-1-Methylethyl Acetate	ACGIH	No Established Limit
		OSHA	No Established Limit
		NIOSH	No Established Limit
		Alberta	No Established Limit
		British Columbia	50 ppm TWA 75 ppm STEL
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	50 ppm TWA; 270 mg/m ³ TWA
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit

Electrical Contact Cleaner Aerosol

CAS No.	Ingredient	Source	Value
109-66-0	Pentane	Yukon	No Established Limit
		ACGIH	1000 ppm
		OSHA	1000 ppm, 2950 mg/m ³
		NIOSH	TWA 120 ppm (350 mg/m ³) C 610 ppm (1800 mg/m ³) [15-minute]
		Alberta	600 ppm TWA; 1770 mg/m ³ TWA
		British Columbia	1000 ppm TWA (listed under Pentane, all isomers)
		Manitoba	1000 ppm TWA (listed under Pentane, all isomers)
		New Brunswick	600 ppm TWA; 1770 mg/m ³ TWA 750 ppm STEL; 2210 mg/m ³ STEL
		Newfoundland and Labrador	1000 ppm TWA (listed under Pentane, all isomers)
		Nova Scotia	1000 ppm TWA (listed under Pentane, all isomers)
		Northwest Territories	600 ppm TWA (listed under Pentane, all isomers) 750 ppm STEL (listed under Pentane, all isomers)
		Nunavut	600 ppm TWA (listed under Pentane, all isomers) 750 ppm STEL (listed under Pentane, all isomers)
		Ontario	1000 ppm TWA
		Prince Edward Island	1000 ppm TWA (listed under Pentane, all isomers)
		Quebec	120 ppm TWAEV; 350 mg/m ³ TWAEV
		Saskatchewan	600 ppm TWA 750 ppm STEL
Yukon	600 ppm TWA; 1800 mg/m ³ TWA 750 ppm STEL; 2250 mg/m ³ STEL		
110-54-3	Hexane	ACGIH	50 ppm
		OSHA	500 ppm, 1800 mg/m ³
		NIOSH	TWA 50 ppm (180 mg/m ³)
		Alberta	50 ppm TWA; 176 mg/m ³ TWA
		British Columbia	20 ppm TWA
		Manitoba	50 ppm TWA
		New Brunswick	50 ppm TWA; 176 mg/m ³ TWA
		Newfoundland and Labrador	50 ppm TWA
		Nova Scotia	50 ppm TWA
		Northwest Territories	50 ppm TWA 62.5 ppm STEL
		Nunavut	50 ppm TWA 62.5 ppm STEL
		Ontario	50 ppm TWA
		Prince Edward Island	50 ppm TWA
		Quebec	50 ppm TWAEV; 176 mg/m ³ TWAEV
		Saskatchewan	50 ppm TWA 62.5 ppm STEL
		Yukon	100 ppm TWA; 360 mg/m ³ TWA 125 ppm STEL; 450 mg/m ³ STEL
124-38-9	Carbon dioxide	ACGIH	5000 ppm 30,000 ppm
		OSHA	5000 ppm, 9000 mg/m ³
		NIOSH	TWA 5000 ppm (9000 mg/m ³) STEL: 30,000 ppm (54,000 mg/m ³)
		Alberta	5000 ppm TWA; 9000 mg/m ³ TWA 30000 ppm STEL; 54000 mg/m ³ STEL
		British Columbia	5000 ppm TWA 15000 ppm STEL
		Manitoba	5000 ppm TWA 30000 ppm STEL
		New Brunswick	5000 ppm TWA; 9000 mg/m ³ TWA 30000 ppm STEL; 54000 mg/m ³ STEL
		Newfoundland and Labrador	5000 ppm TWA 30000 ppm STEL
		Nova Scotia	5000 ppm TWA 30000 ppm STEL
		Northwest Territories	5000 ppm TWA 30000 ppm STEL
		Nunavut	5000 ppm TWA 30000 ppm STEL
		Ontario	5000 ppm TWA 30000 ppm STEL
		Prince Edward Island	5000 ppm TWA 30000 ppm STEL
		Quebec	5000 ppm TWAEV; 9000 mg/m ³ TWAEV 30000 ppm STEV; 54000 mg/m ³ STEV

Electrical Contact Cleaner Aerosol

CAS No.	Ingredient	Source	Value
		Saskatchewan	5000 ppm TWA 30000 ppm STEL
		Yukon	5000 ppm TWA; 9000 mg/m ³ TWA 15000 ppm STEL; 27000 mg/m ³ STEL
64742-49-0	Naphtha (petroleum), hydrotreated light	ACGIH	100 ppm
		OSHA	No Established Limit
		NIOSH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
Yukon	No Established Limit		
68410-97-9	Distillates (petroleum), light distillate hydrotreating process, low-boiling	ACGIH	No Established Limit
		OSHA	No Established Limit
		NIOSH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
Yukon	No Established Limit		

Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes Protective safety glasses recommended

Skin Avoid skin contact. Protective gloves recommended.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any

Electrical Contact Cleaner Aerosol

vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

Information on basic physical and chemical properties

Physical State	Liquid
Color	Clear
Odor	No available information
Odor threshold	No available information
Melting point / freezing point	No available information
Initial boiling point and boiling range	144°F / 62°C
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: LEL = 1.2%
	Upper Explosive Limit: No available information
Flash Point	19°F / -7°C (TCC)
Auto-ignition temperature	750.2°F / 399°C
Decomposition temperature	No available information
pH	No available information
Viscosity	No available information
Solubility in Water	No available information
Partition coefficient n-octanol/water (Log Kow)	No available information
Vapor pressure (Pa)	No available information
Relative Density	0.72
Vapor Density	> 1.0
Evaporation rate (Ether = 1)	>2 (n-butyl acetate = 1)
VOC Content	720 g/l
Oxidising properties	No available information
Explosive properties	No available information
% Volatile	100%

Other information

No other relevant information.

Section 10. Stability and reactivity

Reactivity

Hazardous Polymerization will not occur.

Chemical stability

Stable under normal circumstances.

Possibility of hazardous reactions

No available information

Conditions to avoid

Excessive heat and open flame.

Incompatible materials

Strong oxidizing agents and acids.

Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
2-methylpentane - (107-83-5)	No data available.	No data available.	No data available.	No data available.	No data available.
Naphtha (petroleum), hydrotreated light - (64742-49-0)	> 5,000.00, Rat - Category: NA	>2,000.00, Rabbit - Category: 5	No data available.	No data available.	No data available.
Distillates (petroleum), light distillate hydrotreating process, low-boiling - (68410-97-9)	No data available.	No data available.	No data available.	No data available.	No data available.
Pentane - (109-66-0)	5,000.00, Mouse - Category: 5	3,000.00, Rabbit - Category: 5	364.00, Rat - Category: NA	No data available.	No data available.
Carbon dioxide - (124-38-9)	No data available.	No data available.	No data available.	No data available.	No data available.
2-Methoxy-1-Methylethyl Acetate - (108-65-6)	5,155.00, Rat - Category: NA	>2,000.00, Rabbit - Category: 5	No data available.	No data available.	No data available.
Hexane - (110-54-3)	25,000.00, Rat - Category: NA	3,000.00, Rabbit - Category: 5	No data available.	No data available.	48,000.00, Rat - Category: NA

Carcinogen Data

CAS No.	Ingredient	Source	Value
107-83-5	2-methylpentane	IARC	No
		ACGIH	A3
108-65-6	2-Methoxy-1-Methylethyl Acetate	IARC	No
		ACGIH	No Established Limit
109-66-0	Pentane	IARC	No
		ACGIH	No Established Limit
110-54-3	Hexane	IARC	No
		ACGIH	No Established Limit
124-38-9	Carbon dioxide	IARC	No
		ACGIH	No Established Limit

CAS No.	Ingredient	Source	Value
64742-49-0	Naphtha (petroleum), hydrotreated light	IARC	No
		ACGIH	No Established Limit
68410-97-9	Distillates (petroleum), light distillate hydrotreating process, low-boiling	IARC	No
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	2	Suspected of damaging fertility.
STOT-single exposure	---	Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-repeated exposure	1	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	1	May be fatal if swallowed and enters airways.

Possible routes of entry:

Inhalation, ingestion, skin contact, and skin absorption.

Symptoms and effects, both acute and delayed:

Reproductive or genetic defect hazard. Treat symptomatically.

Inhalation May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Skin Causes mild skin irritation.

Section 12. Ecological information

Toxicity

Toxic to aquatic life with long lasting effects.

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
2-methylpentane - (107-83-5)	No data available.	No data available.	No data available.
Naphtha (petroleum), hydrotreated light - (64742-49-0)	No data available.	2.60, Chaetogammarus marinus	No data available.
Distillates (petroleum), light distillate hydrotreating process, low-boiling - (68410-97-9)	No data available.	No data available.	No data available.
Pentane - (109-66-0)	100.00, Oncorhynchus kisutch	9.74, Daphnia magna	No data available.
Carbon dioxide - (124-38-9)	No data available.	No data available.	No data available.
2-Methoxy-1-Methylethyl Acetate - (108-65-6)	161.00, Pimephales promelas	501.00, Daphnia magna	> 1,000, Pseudokirchnerella subcapitata
Hexane - (110-54-3)	12.51, Oncorhynchus mykiss	21.85, Daphnia magna	9.29, Pseudokirchneriella subcapitata

Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

No available information

Mobility in soil

No available information

Results of PBT and vPvB assessment

This product contains no PBT/vPvB/vPvM chemicals.

Other adverse effects

No available information

Section 13. Disposal considerations

--

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.

Section 14. Transport information
--

Not regulated for packages under 5L (1.3 gallons) or 5.0 kg (11 lbs).

Classification Method: Classified as per Part 2, Sections 2.1-2.8 of the Transportation of Dangerous Goods Regulations.

DOT (Domestic Surface Transportation)

UN number	UN1950
UN proper shipping name	Combustible liquid, n.o.s., (2-methylpentane)
Transport hazard class(es)	Combustible liquid
Sub Class	Not Applicable
Packing group	III

TDG (Domestic Surface Transportation)

UN number	Not Regulated
UN proper shipping name	Not Regulated
Transport hazard class(es)	Combustible liquid
Sub Class	Not Applicable
Packing group	Not Applicable

IMO / IMDG (Ocean Transportation)

UN number	Not Regulated
UN proper shipping name	Not Regulated
Transport hazard class(es)	Not Applicable
Sub Class	Not Applicable
Packing group	Not Applicable

ICAO/IATA

UN number	Cons Com, ID 8000, Class 9, LTD QTY, Per SP A112
UN proper shipping name	Not Regulated
Transport hazard class(es)	Not Applicable
Sub Class	Not Applicable
Packing group	Not Applicable

Environmental hazards

IMDG Marine Pollutant: Yes; (2-methylpentane)

Special precautions for user

No available information

Section 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

This product has been classified in accordance with US OSHA’s Hazard Communication Standard (1910.1200) revised 2024 and Canadian Hazardous Products Regulations (SOR/2015-17 amended 2022-12-15) (GHS revision 7) and the SDS contains all of the information required by those regulations.

All components of this material are either listed or exempt from listing on the TSCA Inventory.

All components of this material are either listed or exempt from listing on the DSL or NDSL Inventories.

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

Hexane

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

Hexane

Proposition 65 Label Warning:



WARNING: This product can expose you to chemicals including [Hexane], which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Section 16. Other information

Revision Date

13 October, 2025

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H224 Extremely flammable liquid and vapor.

H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness and dizziness.

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

End of Document