

# Polywater® ZipSeal™

## FOAM DUCT SEALANT



Polywater ZipSeal foam duct sealant

A Closed-Cell Foam  
Duct Sealing System  
for Conduits up to 2”

### PRODUCT BENEFITS

- **Protects:** Keeps water, gases, and rodents out of conduits.
- **Quick Installation:** Installs in just 45 seconds.
- **Reenterable:** Installed ZipSeal is quickly removed and resealed if necessary.
- **Multiple Seals:** One kit seals up to five 2-in/50-mm conduits.
- **Meets NEC Code Requirements:** 2014 NEC Articles 225.27, 230.8, 300.5 (G), 300.7 (A) on Raceway Seals, 501.15 (B)(2).

### Efficiently Seals Small Conduits and Innerducts

ZipSeal™ Foam Duct Sealant is a practical and efficient way to seal small conduits and communication innerducts. The revolutionary Zip-Disc™ insert traps the foaming liquid in its open-cell (center) area, ensuring a solid seal.



Pliable Zip-Disc surrounding cable



Foam Zip-Disc inserted in conduit



ZIP-50KIT1G components

## For Small Conduits and Innerduct Applications

Polywater ZipSeal is recommended for small conduits and communication innerduct applications. ZipSeal comes in a side-by-side 50-mL cartridge with a 1:1 mixing ratio. A TOOL-50-11 is needed to apply the ZipSeal two-part foam. Each kit comes with all the components required for a quick, strong duct seal, including the unique Zip-Disc for fast and easy application.

### POLYWATER ZIPSEAL

Catalog #	Package Description	Units/Case
ZIP-50KIT1	1 - 50-mL cartridge; 2 - mixing nozzles; 2 - pairs of gloves; 5 - 2-in/5-cm Zip-Discs 1 - instruction sheet	1
ZIP-50KIT1G*	Same as kit above, includes TOOL-50-11	1
ZIP-50KITB6	6 - ZIP-50KIT1	1
TOOL-50-11	Dispensing tool for 50-mL cartridge	1
MXR-20T-10	10-pack mixing nozzles	1

\*International export regulations prohibit inclusion of the dispensing tools in kits. Please order the tool (cat # TOOL-50-11) separately for the international destinations.

### SPECIFICATIONS AND APPLICATIONS:

- **For Ducts and Conduits:** A fast, flexible, efficient, code-compliant way of sealing duct to protect outside plant.
- **Preferred Sealant:** Easier to install than duct putty, and won't sag over time.
- **Water Head:** Holds up to 10 feet (3.0 m) water head pressure.
- **Seals Quickly:** Sealant will harden in 5 to 7 minutes.
- **Unique Zip-Disc:** The Zip-Disc allows for effective horizontal or vertical installations.
- **Multi-Use Cartridge:** May be resealed for future use.
- **Compliant:** Complies with TIA-758-B Standard 5.1.1.2.8, 5.4.2.3, and 7.4.8.1.

#### CONTACT US

1-800-328-9384 Toll Free

1-651-430-2270 Main

1-651-430-3634 Fax

email: [support@polywater.com](mailto:support@polywater.com)

**IMPORTANT NOTICE:** The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct, indirect, or consequential damages resulting from product's use, regardless of the legal theory asserted.

American  
**Polywater**<sup>®</sup>  
Corporation

11222 60th Street N | Stillwater, MN 55082 USA